



PRODUCT DESCRIPTION

To create our popular Acclaim™, we merged contemporary design, natural-looking LED lighting, and a highly versatile built-in defogger — making shaving easier than ever and revolutionizing how you experience the shower.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass, suitable for wet locations including showers. Mirror shall have built in defogger to keep glass clear and uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 3-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Integrated defogger
- Suitable for wet environments, including showers
- Environmentally sustainable
- Energy efficient
- Fast lead times
- ADA compliant
- 3-year limited warranty
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Down light

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- Replaceable LEDs
- 604 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Defogger serves as safety backing
- Low voltage (12V)

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; transformer must be installed in a dry location, not behind mirror and at least 4 feet from wet environment, but within 25' of mirror
- Driver enclosure box requires recess for mounting
- Controlled by non-dimming on/off wall switch; light and defogger operate together
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Power Requirements
ISF-11.75x11.75-DF	11.75"W x 11.75"H x 2.85"D (298mm x 298mm x 72mm)	120/240 VAC, 14W
ISF-11.75x23.75-DF	11.75"W x 23.75"H x 2.85"D (298mm x 603mm x 72mm)	120/240 VAC, 32W
ISF-12.00x28.00-DF-DL***	12"W x 28"H x 4.22"D (305mm x 711mm x 107mm)	120/240 VAC, 33W

*Base model number shown only. To specify additional options, contact residential@electricmirror.com.

**Defogger specification: 24V. Power requirements included in overall lighted mirror power requirements listed above.

***12"x28" model comes standard with downlight

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

