



PRODUCT DESCRIPTION


Reeded glass tubes are paired with ribbed aluminum LED housings in a Gold finish. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to be used in both residential and decorative commercial or hospitality applications.

MEASUREMENTS

DIMENSION : 22.5" L x 22.5" W x 17" H
 MAX OAH : 140" OAH
 CANOPY : 22.5" W x 1.5" H x 22.5" L
 HANGING WEIGHT : 37.5 lb

LAMPING

INPUT VOLTAGE : 120-277V
 LUMENS : 5,400 Rated (3,840 Del.)
 BULB : 12 x 5W LED PCB Integrated , 60W Total
 BULB INCLUDED : (Integrated)
 DIMMABLE : Only at 120V
 CRI : 90 CRI
 COLOR_TEMP : 3000K



*max overall height

FINISHES OPTION



GLASS

Clear Ribbed 144

MATERIAL

Aluminum

RATINGS

cETLus
 Dry Location



ADDITIONAL

SLOPE: 30
 RATED LIFE 25000 Hours
 OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336
 P. 626.956.4200 | F. 626.956.4225 | et2online.com