

FLOS

 FU234423 Anodized Blue Steel


Flauta H1000 Riga

Designed by Patricia Urquiola, 2020

12W - 493lm - 2700K - CRI> 95



Collection of wall-mounted light fittings with dual light emission, available in various lengths. The units are characterised by the surface etching in two refined variations: Flauta Riga, with vertical lines, and Fluta Spiga, characterized by an elegant and sophisticated angular pattern. Rounding out the device is a deflector accessory painted to match the finish of the lamp body. It can be installed as desired on the upper or lower head to create a decorative effect with reflected light. The structure is made of aluminium treated with a chemical conversion process for effective resistance to atmospheric agents. The powder coating of the body is available in various finishes according to the QUALICOAT standard. LED light source included. Integrated 220–240 V electrical power with DALI dimmer. Comes with deflector for optional installation on the upper or lower head. LED light source included. Integrated 220–240 V electrical power with DALI dimmer. Comes with deflector for optional installation on the upper or lower head.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Download

[Mounting instructions](#)



Main specifications

| | |
|-------------------|---------------------|
| EAN | 8059607031025 |
| Mounting | Wall |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | LED Module |
| Power (W) | 12 |
| System power (W) | 12 |
| Source flux (lm) | 493lm |
| System flux (lm) | 493 |

Physical

| | |
|---------------------|---------------------|
| Color | Anodized Blue Steel |
| Net weight (lb) | 5.95 |
| Package volume (in) | 1290.29 |
| IP internal | 40 |
| IP external | 40 |



Photometric

| | |
|--------------------|------------------|
| Lighting type | Indirect, Direct |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 95 |

Electrical

| | |
|--------------------|-----------------------------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Driver | Integrated |
| Dimming type | Dimmable Push, Dimmable DALI 1 |
| Dimming interface | Dimmer Integrated |
| Batteries inside | No |