



09.8406.GX Lacquered Green

Gustave Residential NEW

Designed by Vincent Van Duysen, 2022



Gustave is a portable, self-powered luminaire, specially designed for tabletop lighting applications and other related uses as supplementary lighting. Gustave's compact size encloses a perfect mix of the most innovative optical and light technology and a disruptive engineering, developed in the service of a discretionary purpose of Flos for this project: to create the first portable luminaire on the market with circular design awareness, ecological and honestly conceived against obsolescence. Portable luminaire with autonomous battery, designed for residential applications. Powered by 'Button Type 18650 Li-Ion' batteries (2 units, included inside the product). USB-C charging cable (plug adapter not included). 0-100% sequential regulation by means of capacitive haptic push button.




BOOK AN APPOINTMENT

Main specifications

Mounting	Table
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	2.5
System power (W)	2.5
Source flux (lm)	235
System flux (lm)	169
Efficacy (lm/W)	73

Physical

Color	Lacquered Green	
Cord color	Black	
IP internal	54	



Downl	oad
-------	-----

Family spec sheet	<u>↓</u> ZIP
Mounting instructions	↓ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	↓ ZIP
3D	⊥ ZIP













https://professional.flos.com/en-US/us/product/gustave-residential-09.8406.gx/

09.8406.GX

Schematic light drawing



Beam Angle:		145°
h(m)	E(lx)	D(m)
1	24	6.28
2	6	12.56
3	3	18.84
4	1	25.11
5	1	31 30

30°	44 cd	30°
Lumino 169 lm	ıs flux I	uminaire

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
Beam angle C0-180 (°)	144
Beam angle C90-270 (°)	144

Electrical

Insulation class	III
LED voltage Vf (Vdc)	5
LED current (mA)	180
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Dimmer Integrated
Plug type	Type A
Batteries inside	Yes
Battery type	LI-IO
Charging cycles guaranteed	500
Charging max power	1 A
Charging min time	5.5
Charging socket/connector	USB-C

Notes

Product Battery autonomy: 100% - 6 hours / 50% - 10 hours / 25% - 18 hours. Batteries included. USB-A / USB-C Cable included. Adapter 5V, min 2A not included.

Accessories & Power Supply



REQUIRED

RF25965

Adapter 5V. Min 2A | EUR USA UK



REQUIRED

RF27576

Adapter 5V. Min 2A. EUR / USA /



Pack 2x Battery for Gustave	08.0744.00
Residential	
Cable for Gustave Residential	08.0761.14
USB-A/USB-C	
Cable for Gustave Residential	08.0761.30
USB-A/USB-C	



Electrical

08 0744 00

Pack 2x Battery for Gustave Residential



Cable

08 0761 14

Cable for Gustave Residential USB-A/USB-C



Cable

08.0761.30

Cable for Gustave Residential USB-A/USB-C