

HERKNER COLLECTION

COLLAR Ø300// pendant, us model

Designed by Sebastian Herkner

PRODUCT







// Grey

COLORS





DESCRIPTION

Collar Lamp is the German designer Sebastian Herkner's first product for GUBI. Collar Lamp is a series of pendent lights that combines mouth blown glass and an aluminum "collar", used as a reflector, which gives it an iconic strong character. The lamp looks great as an individual lamp but by mixing colours and sizes it gives possibilities for strong personal and playful installations.

VERSION - COLLAR Ø300


Colour codes are indicative.

- Fabric cable is black // Canopy is black lacquered // Gloss level Shade 2 / Glass top 10

- Sand / Shade NCS S 1502-Y / Glass top NCS S 3005-Y20R / White inside RAL 9003
- Black / Shade NCS S 8500-N / Glass top NCS S 9000-N / White inside RAL 9003
- Grey / Shade NCS S 2005-B80G / Glass top NCS S 5005-B80G / White inside RAL 9003
- Terracotta / Ghade NCS S 4030-Y70R / Glass top NCS S 7020-Y70R / White inside RAL 9003
- Taube / Shade NCS S 5502-Y / Glass top NCS S 7502-Y / White inside RAL 9003

VERSION

Order item - look for part number in the pricelist.



FACTS

MATERIAL

Shade: Wet lacquered steel Glass: Mouthblown opal glass lacquered on top Canopy: Powder coated aluminum

MEASUREMENT - Lx Wx H mm Lamp height: 5,6 inches Shade diameter: dia 11,8 inches Canopy diameter: dia 4,5 inches Canopy hight: 2,2 inches

Cable length, exposed: APP. 157 inches

WEIGHT ITEM - LAMP INCL. WIRE Approx. 6.2 lb

PACKAGING TYPE Cardboard box

PACKAGING MEASUREMENT - L x W x H cm L: 16,5 x W: 13,8 x H: 88,6 inches

WEIGHT PACKAGING - MATERIAL TYPE (recycleable)

- LD-EPE foam: 0,5 lb
- EPE bag: 1 oz
- PE polybag: 0,035 oz - Cardboard inside: -
- Cardboard outside, 5ply Corrugated: 1,5 lb

WEIGHT INCL. PACKAGING - *TOTAL* Approx. 8,2 lb

NUMBER OF PARCELS 1 pcs.

COLLAR Ø300// PENDANT, US MODEL

GUBI®

HERKNER COLLECTION

Designed by Sebastian Herkner		
ACCESSORIES		Bulb requirements: - Socket: E26 base - Bulb type: G16.5 - Recommended wattage: 40 W
ENVIRONMENT		- Max wattage: 40 W
		*Lightbulb not included
- TESTS		- US voltage: 120 V - Freqvency: 60 Hz
		- Supply voltage: AC power ~
- CERTIFICATION AND LABELS		- Normally Closed: 1P20
CE-CERTIFIED UL-CERTIFIED		- Isolation class II / Double insulated
SAFETY INSTRUCTIONS If the cord or plug is damaged, unplug it from the socker repaired by a qualified Electrician. Instructions document no. 62-20-001-04	et with dry hands. Do not use the lamp until it is	Luminaires accepted for mounting or
nist details declinent no. 02 20 001 01		
<image/> <section-header><section-header><section-header><text><text><text><text><text><text><text></text></text></text></text></text></text></text></section-header></section-header></section-header>	GUBI® ASSEMBLY INSTRUCTIONS for COLLAR PENDANT 008-013xx / 008-023xx	Mark for Canada and the U.S.
DATE TRANSPORTED IN TERM AND 10 YEAR OF THE LEARNED GROUP, OH DATEORN 10 YEAR ON THE AND THE ADDRESS OF THE ADDRESS OF THE CALCED SEA OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE CALCED SEA OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE CALCED SEA OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRESS OF THE ADDRE		
GUE A / S GUE A / S FOR WORE AN OPAMATON GRACOM		
42 20 001 04 Mounting Inst. Caller Predier Luß.		
Unify instruction of the one of t	<image/> <image/> <image/> <image/> <section-header><section-header></section-header></section-header>	
Step 1 Renore the particular space.	Step 4 • Pack spore, 5 - 20 dayses. • Pack light lubb is turno and turn the power or.	

ted for mounting on a flammable base