

ACCENT SPOT LUMACORE

5536SK-LMA30K

VARIABLE OUTPUT LED 3000K SPOT 120V

The Variable Output LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the user with full control over wattage and beam spread, all in innovative single design.

| DETAILS | |
|-----------|-------------|
| FINISH: | Satin Black |
| MATERIAL: | Aluminum |
| GLASS: | Clear Lens |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 5.8" |
| HEIGHT: | 3.3" |
| DEPTH: | 2.5 |
| WEIGHT: | 1lb |

| LIGHT SOURCE | |
|---------------------------|----------------------------------|
| LIGHT SOURCE: | Integrated LED |
| LED NAME: | 30G4SE-120V |
| WATTAGE: | 12w, 8w, 5w, 3w LED *Included |
| VOLTAGE: | 120v |
| COLOR TEMP: | 3000 |
| CRI: | 80 |
| INCANDESCENT EQUIVALENCY: | 1 x 60w, 45w, 35w, 25w |
| DIMMABLE: | NO |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 18" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 11.5 |
| CARTON WIDTH: | 4.9 |
| CARTON HEIGHT: | 2.8 |
| CARTON WEIGHT: | 1.1 |



PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- A wiring kit and ground spike is supplied.
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optional performance lenses available
- LumaCore Series products carry a lifetime limited warranty

HINKLEY

HINKLEY
33000 Pin Oak Parkway
Avon Lake, OH 44012

PHONE: (440) 653-5500
Toll Free: 1 (800) 446-5539

hinkley.com