

PRODUCT SPECIFICATIONS



Plume 12-Light LED Pendant

Base Item #135008 Configured Item #135008-1000 135008-LED-STND-03-03

FINISH ACCENT
Mahogany - 03 Mahogany - 03

OVERALL HEIGHT LAMPING
Standard: 18.00" - 100.00"

LED

*Image shown does not correspond to selected options

OPTIONS

FINISH	ACCENT	OVERALL HEIGHT	LAMPING
Mahogany - 03 Bronze - 05 Dark Smoke - 07 Burnished Steel - 08 Black - 10	Mahogany - 03 Bronze - 05 Dark Smoke - 07 Burnished Steel - 08 Black - 10	18.00" - 100.00"	LED

Natural Iron - 20

Vintage Platinum - 82 Soft Gold - 84

Gold - 25

Sterling - 85

SPECIFICATIONS

Vintage Platinum - 82

Natural Iron - 20

Soft Gold - 84 Sterling - 85

Gold - 25

Plume 12-Light LED Pendant

Base Item #: 135008 Configured Item #: 135008-1000 135008-LED-STND-03-03

Circular adjustable height cable-hung LED pendant light. Choose a finish for the canopy and fixture frame and an accent for the metal diffuser shields.

- Handcrafted to order by skilled artisans in Vermont, USA
- Lifetime Limited Warranty when installed in residential setting
- Slope ceiling adaptable to 45 degrees (cable)

Dimensions

| 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 10.00" | 1

LED Lamping Dedicated

LED: 51 Watt CCT: 3000k CRI: 85 Input: 120 - 277V Dimming: line volt

Input: 120 - 277V 50/60Hz Dimming: line voltage, ELV Delivered Lumens: 1800* LED Source Lumens: 4320 IES Files Available: N

* Not photometric tested, calculated from similar product

Location Rating

Indoor Damp

Safety Rating UL, CUL listed

Copyright © 2021 Hubbardton Forge. All Rights Reserved. 800-826-4766 | https://www.hubbardtonforge.com