



EW71412-BK  
Black



EW71412-GY  
Gray

**SPECIFICATION DETAILS**

\* For custom options, consult factory for details.

<b>Fixture Dimensions</b>	W12" x H4-1/2" x E1"
<b>Light Source</b>	AC LED Module
<b>Wattage</b>	23W
<b>Total Lumens</b>	1600lm
<b>Delivered Lumens</b>	BK-286lm; GY-369lm;
<b>Voltage</b>	120V
<b>Color Temperature</b>	3000K
<b>CRI (Ra)</b>	90CRI
<b>Optional Color Temps</b>	2700K - 5000K Available, Minimum Order Quantities Apply
<b>LED Rated Life</b>	50,000 hours
<b>Dimming</b>	100% - 10%, ELV Dimmer (Not Included)
<b>Diffuser Details</b>	Frosted Glass Diffuser
<b>Location</b>	Wet
<b>Mounting Style</b>	All Orientation; Wall;
<b>Warranty</b>	5 Years
<b>ADA Compliant</b>	Yes

**DESCRIPTION**

This family of exterior wall-mounted fixtures is available in a variety of geometric forms: circle, square, and two different rectilinear configurations. Light is directed downward from a recess, and the incline allows the glow to radiate gradually. Vanishingly thin and ideal for egress, courtesy, and grace lighting. Optional stone inlays offer additional opportunities for customizing to complement different wall surfaces.

