louis poulsen

AJ ROYAL

Designed by Arne Jacobsen



Description

The pendant comes in three sizes and is characterized by the ridges on top that allow a gentle light to exude upwards. In the new, energy-saving LED version, all three sizes come with a diffuser, which offers a smoother, 100% glare-free lighting.

Variants	VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
	10000151333	BLACK	14.6 / 6.5 / 14.6 IN / 4.5 LB
	10000151334	WHITE	14.6 / 6.5 / 14.6 IN / 4.5 LB
	10000151337	BLACK	14.6 / 6.5 / 14.6 IN / 4.5 LB
	10000151340	WHITE	14.6 / 6.5 / 14.6 IN / 4.5 LB
	10000151341	BLACK	19.7 / 8.8 / 19.7 IN / 13.1 LB
	10000151342	WHITE	19.7 / 8.8 / 19.7 IN / 13.1 LB
	10000151345	WHITE	19.7 / 8.8 / 19.7 IN / 13.1 LB
	10000151347	BLACK	19.7 / 8.8 / 19.7 IN / 13.1 LB

Materials & Finishes

MATERIALS

Shades: Spun aluminum. Rings: Steel. Diffuser: Frosted acrylic.

FINISHES

louis poulsen

White or black, wet painted.

Mounting

Cord type: 18 AWG braided fabric covered power cord. Cord length: 12'. Black canopy and cord for black pendant, white canopy and cord for white pendant. For mounting instructions, see download section on the product detail page.

Information

Electrical:

System Wattage: 8W or 30W LED Wattage: 7 W or 28 W Delivered lumens: 508 - 2,309 Efficacy: 63.5 lm/W - 77.0 lm/W

Certifications:

cULus, Damp Location Protection class IP20


Controllability: 0-10V Dimming

Color Rendering: Ra≥90 For the E-socket product variants, bulbs are not included. LED light


source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOUNCE	VOLTAGE/FRQ	LUIVIEIN	FEATURES	CABLE
10000151333	LED 3000K	120-277V/60HZ	951	Phase+dim 0-10v	Black textile and wire
10000151334	LED 3000K	120-277V/60HZ	1125	Phase+dim 0-10v	White textile and wire

louis poulsen

10000151337	LED 2700K	120-277V/60HZ	930	Phase+dim 0-10v	Black textile and wire
10000151340	LED 2700K	120-277V/60HZ	1100	Phase+dim 0-10v	White textile and wire
10000151341	LED 3000K	120-277V/60HZ	1955	Phase+dim 0-10v	Black textile and wire
10000151342	LED 3000K	120-277V/60HZ	2242	Phase+dim 0-10v	White textile and wire
10000151345	LED 2700K	120-277V/60HZ	2309	Phase+dim 0-10v	Black textile and wire
10000151347	LED 2700K	120-277V/60HZ	1898	Phase+dim 0-10v	White textile and wire

Specification Notes

a. 14.6 IN size available only in 16W.b. 19.7 IN size available only in 30W.