

shown in Brushed Nickel  
with Mahogany blades



# Dagny LK

*Designed in 2013*



With clean, fluid lines, the Dagny LK 360° rotational fan is a striking centerpiece in any space. Its movement about its cylindrical center housing is smooth and quiet. Dagny LK's dual fan heads can be infinitely positioned in 180-degree arcs for optimum and customized air movement. As the angle between the fan heads and the horizontal support rods is increased, so does the speed of Dagny LK's axial rotation. Matthews rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed from cast aluminum and heavy stamped steel, the Dagny LK carries a limited lifetime warranty. This model is also available without a light kit as the **Dagny**.

## Product Features

 American Labor	 AC Motor	 360° Rotation	 Safety Cage Compatible	 Damp Location	 Soothing White Noise	 LED Lamp	 Remote Control	 Unpack Shipping
---	---	--	---	--	--	---	---	--



shown in Brushed Nickel with Barn Wood Blades



shown in Brushed Nickel with Mahogany Blades



shown in Textured Bronze with Metal Blades and Decorative Cage



shown in Textured Bronze with Barn Wood Blades



shown in Matte Black with Matte Black Blades

# DAGNY LK

## FINISH AND BLADE OPTIONS

SKU#	<b>DGLK-XX-XXXX</b> (Model+Finish+Blade)	
Standard Finishes	Brushed Nickel Matte Black Textured Bronze	<b>BN</b> <b>BK</b> <b>TB</b>
<b>NEW</b>	Blade Styles and Material	<b>Solid Wood / Barn Wood</b> <b>WDBW</b> <b>Solid Wood / Mahogany</b> <b>WD</b> <b>Solid Wood / Matte Black</b> <b>WDBK</b> <b>Metal w/ Decorative Cage</b> <b>MTL</b> <b>Metal w/ Safety Cage</b> <b>MSAF</b>

## TECHNICAL SPECS

Overall Drop	14 inches / 41 cm + downrod length
Fan Weight	22 lbs
Voltage	110 (Contact us for 220 conversion)
Motor Type	AC
Rotation	Yes
Downrods Lengths <i>Field cuttable, Non-Threaded</i>	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183
Downrod Diameter	1 inch
Environment	Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible
Ambience	Soothing White Noise
Safety Certification	UL / CUL
Warranty	Limited Lifetime

## NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA

Fan Head Options	Solid Wood	Metal with Guard
Fan Diameter	41 inches / 104 cm	39 inches / 99 cm
Fan Blade Diameter	16 inches / 41 cm	13 inches / 33 cm
Guard Options	No Cage Option	Safety Cage or Decorative Cage
RPM (Low / High)	757 / 1256	1069 / 1442
CFM (Low / High)	2557 / 4171	1844 / 3067
Watts (High)	87.36	80.50
CFM/Watt (High)	50.00	39.00
Blade Pitch	19°	31°

## LIGHT KIT PHOTOMETRICS

Lamping (Replaceable)	Integrated LED
Remote Dimmable	Yes
Delivered Temperature in K	2969
Delivered Lumens	523.7
CRI	90
Watts	18
Hours	50,000

Light kit longevity if used 6 Hours/Day: 22.8 Years

## STANDARD EQUIPMENT

- One downrod of 10 inches / 25 cm
- Vaulted ceiling canopy for up to 29°


Black 3-speed RF remote control with reverse



## ACCESSORY

Decora-style, 3-speed, non-dimmable wall control





### CEILING PITCH TABLE

0/12	0 degrees
1/12	4.76 degrees
2/12	9.46 degrees
3/12	14.04 degrees
4/12	18.43 degrees
5/12	22.62 degrees
6/12	26.57 degrees
7/12	30.26 degrees
8/12	33.69 degrees
9/12	36.87 degrees
10/12	39.81 degrees
11/12	42.51 degrees

### CEILING HEIGHT / DOWNROD TABLE

Ceiling Height	Downrod Lengths <i>Field cuttable. Non-threaded</i>
10 ft or less	5 inches / 13 cm <i>Use safety cages if applicable</i>
10 -12 feet	10 inches / 25 cm
13 feet	20 inches / 51 cm
14 feet	30 inches / 76 cm
15 feet	48 inches / 122 cm
16 feet +	72 inches / 183 cm

#### Matthews Fan Company

1881 Industrial Drive  
Libertyville, IL 60048  
Tele: 847.680.9043  
Fax: 847.680.8140  
www.matthewsfanco.com

© 2021 Matthews Fan Company. All rights reserved.

