

COUNTERMAX MX-L-120-3K BASIC I UNDERCABINET 3K BASIC

89892 / 89893 / 89894 / 89895 / 89896 / 89897

- 3 Color Temperature Options: 4000K, 3000K, and 2700K
- Dimmable using Triac and ELV Dimmers
- Linkable end-to-end or with MX Interlink cord
- Link up to 750 max watts from one supply
- 50,000 hours rated life
- 120° rotation
- CRI 90+
- Suitable for Dry location
- ETL cETL

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____




PRODUCT DESCRIPTION

Switch between 3 color temperatures: 4000K, 3000K, and 2700K. All in a 90 CRI for accurate color rendering. The 3K has a patented gimbal designed to allow light to be directed where desired as well as a patented LED strip for even light distribution.



- Patent gimbals to direct illumination



MEASUREMENTS

| MODEL | DIMENSION | HANGING WEIGHT | CRI |
|-------|--------------------|----------------|-----|
| 89892 | 6"L x 3.5"W x 1"H | 0.36 lb | 90+ |
| 89893 | 12"L x 3.5"W x 1"H | 1.32 lb | 90+ |
| 89894 | 18"L x 3.5"W x 1"H | 1.32 lb | 90+ |
| 89895 | 24"L x 3.5"W x 1"H | 2.26 lb | 90+ |
| 89896 | 30"L x 3.5"W x 1"H | 2.84 lb | 90+ |
| 89897 | 36"L x 3.5"W x 1"H | 3.26 lb | 90+ |

LAMPING

| MODEL | BULB TYPE | COLOR TEMPERATURE | LUMENS INIT. | DEL | INPUT | DIMMABLE |
|-------|------------------------------|-------------------|--------------|------|-------|----------|
| 89892 | (1) 3W PCB LED (Integrated) | 2700/3000/4000K | 200 | 175 | 120V | Triac CL |
| 89893 | (1) 5W PCB LED (Integrated) | 2700/3000/4000K | 320 | 275 | 120V | Triac CL |
| 89894 | (1) 8W PCB LED (Integrated) | 2700/3000/4000K | 500 | 450 | 120V | Triac CL |
| 89895 | (1) 12W PCB LED (Integrated) | 2700/3000/4000K | 750 | 650 | 120V | Triac CL |
| 89896 | (1) 16W PCB LED (Integrated) | 2700/3000/4000K | 1000 | 900 | 120V | Triac CL |
| 89897 | (1) 20W PCB LED (Integrated) | 2700/3000/4000K | 1250 | 1100 | 120V | Triac CL |

*Showing lumens based on White (WT) finish

INCLUDES

- 3/8" knockouts on back and bottom
- Romex connector
- Mounting screws

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)



MATERIAL:

Aluminum

AVAILABLE SIZE:

6" | 12" | 18" | 24" | 30" | 36"

RATINGS:

ETL cETL
 Dry Location
 Energy Star
 CA Title 24



ADDITIONAL:

RATED LIFE: 40,000 Hours
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC: Report Found Online

*Photometric data is based on 3000K color temperature on White (WT) finish



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

COUNTERMAX MX-L-120-3K BASIC I UNDERCABINET 3K BASIC

ACCESSORIES

Job Name : _____

Job Type : _____

Quantity : _____

Comments : _____



87885 BK, WT
MXInterLink4 Direct Wire Box
2.25"L x 5"W x 1"H



53255
Plastic Wire Clips (Package of 10)
1"L x 0.5"W x 0.25"H



9" **87876 BK, WT**
18" **87877 BK, WT**
24" **87878 BK, WT**
MXInterLink4 Connector Cord



87880 BK, WT
MXInterLink4 Connector Cord 72"
72"L x 1"W x 0.5"H