

INSTALLATION INSTRUCTION FOR 4177

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

1. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
2. Shut off the power at the circuit breaker and remove old fixture, including the mounting hardware.

ASSEMBLING THE FIXTURE

3. Place the diffuser (J) onto the fixture body (L) and secure by bending the small glass holder tabs (K).
4. Place hook (H) of the rods (G) into the loop (I). Then loop (F) of the rods (G) into the hook (E).

MOUNTING THE FIXTURE (Fig.1)

5. Secure circular strap (B) to junction box using junction box screws (A) (Size: #8-32*0.6"L). The side of the mounting bar marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

6. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire directly to the circular strap (B) using the green screw provided. After the wires are connected, tuck them carefully inside the junction box.

COMPLETING THE INSTALLATION

7. Raise the fixture (C) over the circular strap (B) and secure with mounting screws (D).
8. Install (3) three medium base bulbs up to 100 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification.

DO NOT EXCEED THE SPECIFIED WATTAGE!
(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. Return the power to the junction box and test the fixture.

