

# INSTALLATION INSTRUCTIONS FOR FIXTURE#4107-172/84

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**  
**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

## ASSEMBLING THE FIXTURE (FIG. 1)

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the old fixture from the ceiling, including the existing mounting hardware.
2. Carefully remove the new fixture from the carton and check that all parts are included as shown in the illustration.
3. Thread the nipple (X) into the coupling (Z) and secure with hex nut;
4. Put the tube (Y), check ring (V), canopy (D), Flat washer (U), lock washer (T) onto the nipple (X) in order, then secure with hex nut (S) tightly;
5. Thread the nipple (H) into the coupling (G) and secure with hex nut.
6. Install the bulbs in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!)**  
**(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**
7. Insert the tube (I), check cover (J), flat washer (K), rubber washer (L), glass diffuser (M), rubber washer (N), flat washer (O) over the nipple (H) and secure with hex nut (R) until snug.
8. Insert the cap (P) over the nipple (H) and secure with finial (Q).

## MOUNTING THE FIXTURE


9. Attach the cross bar (B) to the outlet box using the outlet box screws (A). The side of the cross bar marked "GND" must face out.
10. Raise the fixture body to the outlet box.

## CONNECTING THE WIRES (FIG. 2)

1. At this point, connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate using the green screw provided. After wires are connected, tuck them carefully inside the Junction Box.
2. Attach the fixture body onto the outlet box by protruding mounting screws(C) through mounting holes on the canopy (D) and secure with ball nuts (E).

Your installation is now complete. Return power to the outlet box and test the fixture.

**Fig.1**



**Fig. 2**

