
# AURA

## FR-W2303-72L

72" Ceiling Fan





#### PRODUCT DESCRIPTION

The sublime Aura Smart Ceiling Fan by Modern Forms defines the look and performance you desire in your bedroom, dining, or living area. A 72-inch sweep and a broad array of eight blades transport a swiftly moving surge of air across your room from an overhead silhouette with a cool cutting edge. Each blade is expertly engineered with a subtle curve to push a relaxed, comfortable breeze down over the room. Your remote control will commission one of its six speeds and drive the engine of comfort into your home.

#### **FEATURES**

- · 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Includes BT remote control
- Optional wall control for 3, 4-way control sold separately
- · Compatible with Modern Forms app

## AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 7188/9420 Weighted-Average/High Energy Use (W): 29/43 **Estimated Yearly Energy Cost (\$):** 8 Weighted-Average/High Efficiency (CFM/W): 250 Max RPM: 83

### **ORDER NUMBER**

Model	Hous	ing	Hous	Housing/Blades			
	MB	Matte Black	BN	Brushed Nickel			
FR-W2303-72L	MB	Matte Black	SB	Soft Brass			
	MW	Matte White	SB	Soft Brass			

#### **SPECIFICATIONS**

**Construction:** Aluminum, Steel, ABS Blade: 16° Pitch, 72" sweep .75"W x 6"H included Downrod:

**Mounting Slope:** Up to 30° 80" 33.5 lbs **Hanging Weight: Total Power:** 63W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

125 x 25 sensorless DC motor **Motor Type:** 

# **WIRELESS PERFORMANCE**

Wi-Fi Range: Up to 150 ft\* **Bluetooth Range:** Up to 150 ft\*

## **LUMINAIRE PERFORMANCE**

**Light Source: LED Light Wattage:** 19.5W Lumens/Delivered Lumens: 1600/944 Dimming: Integrated CRI:

**Color Temperature:** 3000K (2700K/3500K options available)

**Rated Life:** 50,000 hours

Example: FR-W2303-72L-SB/MB

For 2700K add "-27"; for 3500K add "-35" before the finish: FR-W2303-72L35SBMB

\*Results may vary based on application and surroundings.

\*This fan comes uni-pack - blade select options are not available

The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

72" Ceiling Fan



## **OPTIONAL ACCESSORIES**

OF HONAL ACCESSORIES				
Bluetooth Wall Control		F-WCBT	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	MOCENNA 0	F-RCBT	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are .75 (in) I.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-GH, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

## SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

## **SLOPED CEILING DEGREE CONVERSION CHART**

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to  $30^{\circ}$  (7/12 pitch). Optional slope kit allows mounting on ceilings up to  $45^{\circ}$  (12/12 pitch). The receiver will mount inside canopy up to  $45^{\circ}$ .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire