WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Niveous

Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Title 24	Finish
PD-52307 7"	3000K 90	9.5W	777	588	Yes	AB Aged Brass BN Brushed Nickel WT White

Example: PD-52307-AB

DESCRIPTION

The Perfect sphere. Niveous reflects the smooth, frosty surface of fresh snow. Enhancing the simple purity of the flawless etched glass, Niveous offers optimized light distribution deploying multiple mid-powered LEDs to achieve an evenly lit globe with mouth blown etched triplex glass.

FEATURES

- Mouth blown etched opal glass provides even illumination
- · Integral swivel for sloped ceilings
- Three 12 inch and one 6 inch downrods included (additionaldownrods available)
- \bullet Driver installed within the Junction Box, driver dimension: 2.95" x 1.88" x
- 1.14"
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000К
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%
Rated Life:	70000 Hours
Standards:	ETL, cETL, Title 24: 2019
	Damp Location Listed
Construction:	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS


RPL-GLA-52307 - Glass for PD-52307 RPL-ROD-IN06-WT - 6" rod - WT finish RPL-ROD-IN12-WT - 12" rod - WT finish RPL-ROD-IN06-BB - 6" rod - AB finish RPL-ROD-IN12-BB - 12" rod - AB finish RPL-ROD-IN06-BN - 6" rod - BN finish



FINISHES



LINE DRAWING



waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. February 2021

WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Niveous

Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Title 24	Finish
PD-52310 10"	3000K 90	13.9W	905	685	Yes	AB Aged Brass BN Brushed Nickel WT White

Example: PD-52310-AB

DESCRIPTION

The Perfect sphere. Niveous reflects the smooth, frosty surface of fresh snow. Enhancing the simple purity of the flawless etched glass, Niveous offers optimized light distribution deploying multiple mid-powered LEDs to achieve an evenly lit globe with mouth blown etched triplex glass.

FEATURES

Mouth blown etched opal glass provides even illumination

· Integral swivel for sloped ceilings

• Three 12 inch and one 6 inch downrods included (additionaldownrods available)

 Driver installed within the Junction Box, driver dimension: 2.95" x 1.88" x 1.14"


5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%
Rated Life:	70000 Hours
Standards:	ETL, cETL, Title 24: 2019
	Damp Location Listed
Construction:	Aluminum hardware with opal glass diffuser

FINISHES

Brushed Nickel Aged Brass White LINE DRAWING



REPLACEMENT PARTS

RPL-GLA-52310 - Glass for PD-52310 RPL-ROD-IN06-WT - 6" rod - WT finish RPL-ROD-IN12-WT - 12" rod - WT finish RPL-ROD-IN06-BN - 6" rod - BN finish RPL-ROD-IN12-BN - 12" rod - BN finish RPL-ROD-IN06-BB - 6" rod - AB finish RPL-ROD-IN12-BB - 12" rod - AB finish

WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Niveous

Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Title 24	Finish
PD-52313 13"	3000K 90	14.1W	907	715	Yes	AB Aged Brass BN Brushed Nickel WT White

Example: PD-52313-AB

DESCRIPTION

The Perfect sphere. Niveous reflects the smooth, frosty surface of fresh snow. Enhancing the simple purity of the flawless etched glass, Niveous offers optimized light distribution deploying multiple mid-powered LEDs to achieve an evenly lit globe with mouth blown etched triplex glass.

FEATURES

Mouth blown etched opal glass provides even illumination

· Integral swivel for sloped ceilings

• Three 12 inch and one 6 inch downrods included (additionaldownrods available)

 \bullet Driver installed within the Junction Box, driver dimension: 2.95" x 1.88" x

1.14"

• 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%
Rated Life:	70000 Hours
Standards:	ETL, cETL, Title 24: 2019
	Damp Location Listed
Construction:	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

RPL-GLA-52313 - Glass for PD-52313 RPL-ROD-IN06-BB - 6" rod - AB finish RPL-ROD-IN12-BB - 12" rod - AB finish RPL-ROD-IN06-BN - 6" rod - BN finish RPL-ROD-IN12-BN - 12" rod - BN finish RPL-ROD-IN06-WT - 6" rod - WT finish RPL-ROD-IN12-WT - 12" rod - WT finish



FINISHES

Aged Brass	Brushed Nickel	White			

LINE DRAWING

