

# FLOS

■ F0288000 Black

## Noctambule Floor 1 Low Cylinder Small Base

Designed by Konstantin Grcic, 2019


18W - 485lm - 2700K



Standing lamps consisting of interconnecting glass modules reaching a height of 2,17 metres (85.43"). Cylindrical and semi-spherical transparent blown glass structure, die cast aluminium base and rings, hydroformed steel internal lateral arms and injection moulded optical opal silicone outer ring diffusers. The power supply cable is 2 metres (78.74") long, with a pedal operated panel used as a dimmer to adjust the light intensity by 10% to 100% in either direction. Wall mounted power supply unit with interchangeable plugs.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                   |                     |
|-------------------|---------------------|
| EAN               | 8059607000847       |
| Mounting          | Floor               |
| Environments      | Indoor dry location |
| Light Source Type | LED                 |
| LED type          | LED Module          |
| Power (W)         | 18                  |
| System flux (lm)  | 485                 |

### Physical

|                     |         |
|---------------------|---------|
| Color               | Black   |
| Cord length (in)    | 71      |
| Net weight (lb)     | 22.71   |
| Package volume (in) | 6880.79 |
| IP internal         | 20      |

### Download


|                       |                       |
|-----------------------|-----------------------|
| Mounting instructions | <a href="#">↓ PDF</a> |
| Mounting instructions | <a href="#">↓ PDF</a> |
| Spare Parts           | <a href="#">↓ PDF</a> |

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional




Replaceable control gear by an end-user



|    |
|----|
| IP |
| 20 |

## Schematic light drawing



Luminous flux Luminaire  
286 lm

### Photometric

|                    |           |
|--------------------|-----------|
| Lighting type      | Total     |
| Light distribution | Symmetric |
| CCT (K)            | 2700      |

### Electrical

|                      |                        |
|----------------------|------------------------|
| Insulation class     | III                    |
| Frequency (Hz)       | 50/60                  |
| Main voltage (Vac)   | 100-240/48             |
| LED voltage Vf (Vdc) | null                   |
| Driver               | Remote included        |
| Dimmable             | Yes                    |
| Dimming type         | Electronic 48V         |
| Dimming interface    | Dimmer Integrated      |
| Plug type            | Type G, Type A, Type C |
| Batteries inside     | No                     |
| Charging min time    | No                     |

## Spare Parts



- |     |                                      |           |
|-----|--------------------------------------|-----------|
| 03. | Terminal cap                         | F0293030A |
| 04. | Fixing screws kit                    | RF0254100 |
| 05. | Ring led diffuser                    | RF27498   |
| 06. | Noctambule Low Cylinder              | F0254000A |
| 07. | Black plug assembly kit & 48V driver | RF3320400 |
| 08. | Switch dimmer 48v pmw 500hz          | RF27549   |
| 09. | Small base                           | F0261030A |

**DOWNLOAD**



F0293030A

Terminal cap



RF0254100

Fixing screws kit



RF27498

Ring led diffuser



F0254000A

Noctambule Low Cylinder



RF3320400

Black plug assembly kit & 48V driver



RF27549

Switch dimmer 48v pmw 500hz



F0261030A

Small base