

# AURORA Ceiling Mount / Wall Sconce

## 3-662-xx

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel



-15 Black



-20 Polished Nickel

**LIGHT SOURCE** 1 x 21.5W LED, 3000K, CRI 90

**LUMINAIRE POWER** 25.1W at 120V

**RATED LIFE** 60000 hr RL

**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K

**LUMEN OUTPUT** Delivered: 1084 lm (LM-79)

**INPUT VOLTAGE** 120V to 277V AC, 50/60Hz

**DRIVER OUTPUT** 700mA, 29.4W max

**DIMMING** TRIAC and ELV dimming at 120V AC;  
0-10V dimming, 100% to 10% current output



**CONSTRUCTION** Plated Steel and Acrylic

**DIFFUSER** Matte White Acrylic

**FINISHES** Black (-15), Polished Nickel (-20), Satin Nickel (-24)

**MOUNTING** 4" Octagonal J-Box\*  
4"x4" Square J-Box\* with single device mud ring  
\*Deep J-Box (Required to house driver)

**STANDARDS** UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598,  
Certified CAN/CSA, STD C22.2 No 250.0.



Dia.

**DIMENSIONS**

**Dia: 13.50"**

**Ext: 4.00"**

**M.C: 6.75" From Top of Fixture**

Order example for standard fixture:

**3-662-xx** (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **3-662-2724**

**27:** 2700K, **35:** 3500K, **40:** 4000K

