

MIRAGE Wall Sconce
3-516-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____




-40 Aged Brass



-24 Satin Nickel

- LIGHT SOURCE** 1 x 12.1W LED, 3000K, CRI 90
- LUMINAIRE POWER** 14.7W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 764 lm (LM-79)
- INPUT VOLTAGE** 120V to 277V AC, 50/60Hz
- DRIVER OUTPUT** 350mA, 14.7W max power
- DIMMING** TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
- CONSTRUCTION** Plated Steel and Acrylic
- DIFFUSER** - Matte White Acrylic
- FINISHES** Satin Nickel (-24), Aged Brass (-40)
- MOUNTING** 2" x 3" J-Box, 4" Octagonal J-Box, 4" Square J-Box with a single device mud ring
- STANDARDS** UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.
- NOTE** Backplate is required



- DIMENSIONS**
- W:** 4.75"
 - H:** 19.125"
 - Ext:** 4.00"
 - M.C:** 16.18" From top of fixture

Order example for standard fixture:
3-516-24 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V to 277V

Order example for optional color temperatures: **3-516-2724**
27: 2700K, **35:** 3500K, **40:** 4000K

