moooi

Random Light II

BERTJAN POT



Random Light II transmits a feeling of simplicity, lightness and a touch of magic in a contemporary style. Due to how they're made, each Random Light is unique. They're never completely round, yet always beautifully transparent and delicate.

Detailing



The open and random texture of the Random Light plays with shadow while it emits a soft glow.

Colours

Black

White

Random Light II / large

Dimensions

Ø105cm | 41.3"



Product

WIDTH 105cm | 41.3"
HEIGHT 105cm | 41.3"
DEPTH 105cm | 41.3"
DIAMETER 105cm | 41.3"

WEIGHT NETTO 2.5kg | 5.51lbs

Packaging

width $110 \text{cm} \mid 43.3$ " height $110 \text{cm} \mid 43.3$ " cubage $1.33 \text{m}^3 \mid 47 \text{ft}^3$ length $110 \text{cm} \mid 43.3$ " weight $13.5 \text{kg} \mid 29.76 \text{lbs}$

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL LIGHTSOURCE TYPE

A++ to E Incandescent

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes

 DIAMETER SHADE
 INPUT VOLTAGE

 105cm | 41.3"
 220-240

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

DIMMABLE LAMPHOLDER

Yes E27

RECOMMENDED LIGHTSOURCE60W MAX type G, 10W LED light included
50000 hours

CABLE COLOUR CABLE LENGTH

Black 400cm | 157.5"; 1000cm | 393.7"

CANOPY

CANOPY CRIPebble II Black, ABS 90

LIGHT DIRECTION LIGHT OUTPUT
All directions 800 lm

Technical cULus

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE

105cm | 41.3"

FREQUENCY

50/60

DIMMABLE

Yes

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS

LIGHT DIRECTION

All directions

LIGHTSOURCE TYPE

Incandescent

NUMBER OF LIGHTSOURCES

-1

INPUT VOLTAGE

110-130

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E26

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CRI

90

LIGHT OUTPUT

800 lm

Random Light II / medium

Dimensions

Ø80cm | 31.5"





Product

width 80cm | 31.5" HEIGHT 80cm | 31.5" DEPTH 80cm | 31.5" DIAMETER 80cm | 31.5" WEIGHT NETTO 1.8kg | 3.97lbs Packaging

width 87cm | 34.3" Height 87cm | 34.3" cubage 0.66m³ | 23.25ft³ Length 87cm | 34.3" weight 5.5kg | 12.13lbs

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL LIGHTSOURCE TYPE
A++ to E Incandescent

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes

 DIAMETER SHADE
 INPUT VOLTAGE

 80cm | 31.5"
 220-240

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

DIMMABLE LAMPHOLDER

Yes E27

RECOMMENDED LIGHTSOURCE60W MAX type G, 10W LED light included
50000 hours

CABLE COLOUR CABLE LENGTH

Black 400cm | 157.5"; 1000cm | 393.7"

CANOPY CRI
Pebble II Black, ABS 90

LIGHT DIRECTION LIGHT OUTPUT
All directions 800 lm

Technical cULus

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL LIGHTSOURCE TYPE
A++ to E Incandescent

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes 1

 DIAMETER SHADE
 INPUT VOLTAGE

 80cm | 31.5"
 110-130

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

DIMMABLE LAMPHOLDER

Yes E26

RECOMMENDED LIGHTSOURCE LIFETIME

60W MAX type G, 10W LED light included 50000 hours

CABLE COLOUR CABLE LENGTH

Black 400cm | 157.5"; 1000cm | 393.7"

CANOPY CRIPebble II Black, ABS 90

All directions

LIGHT OUTPUT

800 lm

Random Light II / small

Dimensions

Ø50cm | 19.7"





Product

WIDTH 50cm | 19.7"

HEIGHT 50cm | 19.7"

DEPTH 50cm | 19.7"

DIAMETER 50cm | 19.7"

WEIGHT NETTO 1.2kg | 2.65lbs

Packaging

width $51cm \mid 20.1$ "

Height $53cm \mid 20.9$ "

Cubage $0.14m^3 \mid 4.87ft^3$ Length $51cm \mid 20.1$ "

Weight $2.5kg \mid 5.51lbs$

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE 50cm | 19.7"

FREQUENCY

50/60

DIMMABLE

Yes

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS

All directions

LIGHTSOURCE TYPE

Incandescent

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE 220-240

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E27

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CRI 90

LIGHT OUTPUT

800 lm

Technical cULus

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL LIGHTSOURCE TYPE A++ to E Incandescent

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes

DIAMETER SHADE INPUT VOLTAGE 50cm | 19.7" 110-130

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

DIMMABLE LAMPHOLDER Yes E26

RECOMMENDED LIGHTSOURCE LIFETIME 60W MAX type C, 10W LED light included 50000 hours

CABLE COLOUR CABLE LENGTH

Black 400cm | 157.5"; 1000cm | 393.7"

CANOPY CRI Pebble II Black, ABS 90

LIGHT DIRECTION LIGHT OUTPUT All directions 800 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is **DIMMER TYPE** compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

Mains dimmable with compatible light source