

ASSEMBLY INSTRUCTIONS FOR YOUR CELESTE PENDANT

IMPORTANT SAFETY INSTRUCTIONS:

- * These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.
- * **WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.**
- * Turn off power at switch before replacing bulbs, making sure fixture has had sufficient time to cool down.
- * If any special control devices are used with this fixture, follow the instructions carefully to assure full compliance with N.E.C. requirements. If there are any questions, contact a qualified electrical contractor.
- * This fixture is U.L. rated for dry locations.

ASSEMBLY INSTRUCTIONS:

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY AT FUSE BOX/ CIRCUIT BREAKER.
2. Remove all parts from carton. Do not throw away any parts.
3. Remove quick link (G) from hang straight (F). Keep quick link (G) attached to loop (H).
4. Remove cross bar (A) (with threaded tube (C) and hang straight (F) attached) from canopy (D) by unscrewing collar (E). Affix cross bar (A) to ceiling outlet box using screws (B) provided.
5. Carefully slide threaded collar (E) down extensions (I) until it rests on threaded tube (J). Carefully slide canopy (D) down extensions (I) until it rests on collar (E).
6. Measure desired drop for fixture to hang and add/remove extension tubes (I). Guide wiring through extension tubes before threading tubes together. ****ADD/REMOVE EXTENSIONS: (Un)Thread the threaded tube of one extension into the threaded opening of the next extension. Make sure wiring is pulled tight when threading extensions together to prevent damage to the wire****
7. Thread bottom extension tube (I) onto the threaded tube (J).
8. Connect hang straight (F) and loop (H) using quick link (G).
9. Lift fixture to ceiling outlet box. Guide wiring through hang straight(F) and threaded tube (C).
10. Make proper electrical connections described in steps 11 - 13. **A LICENSED ELECTRICIAN IS RECOMMENDED.**
11. Attach ground wire from fixture (green or silver in color) to ground wire from outlet box. Fasten wires together with wire nut (O) and tightly wrap connection with electrical tape.
12. Attach hot wire from fixture (black in color or smooth side of wire) to hot wire from outlet box. Fasten wires together with wire nut (O) and tightly wrap connection with electrical tape.
13. Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from outlet box. Fasten wires together with wire nut (O) and tightly wrap connection with electrical tape.
14. Carefully push wire connections back into the ceiling outlet box.
15. Slide canopy (D) up extension tubes (I) and hold firmly against ceiling. Slide collar (E) up extension tubes (I) and thread onto hang straight (F), securing canopy (D) against ceiling.
16. Install (12) 40W MAX Type A15 (short neck), medium base bulbs into sockets.
17. To attach glass shades, first loosen threaded washer (K) and move shade cap (L) up. Once loosened, slide glass shade (N) over the bulb and shade retention clip (M). Slide shade cap (L) back down over the glass shade (N). Then tighten threaded washer (K) until hand tight. (This will tighten the shade retention clip (M) holding the glass shade (N) in place).

ASSEMBLY INSTRUCTIONS FOR YOUR CELESTE PENDANT

