

CANDLE

4W | 360 lm | 2500K

CAND-4W-2500K-E12-NT-120V

Candle 4W 2500K E12 Non-Tinted US LED Bulb


tala

The Candle light bulb by Tala is a powerful yet slender light bulb, perfect for chandeliers or table lamps. The classic design comes complete with energy efficient LED technology, lasting an average of 5-10 years based on daily usage.




PHYSICAL

Bulb diameter:	1 3/8in
Bulb length:	3 7/8in
Glass shape:	C11
Base:	E12
Materials:	Glass & nickel
Glass finish:	Clear
Weight:	15g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80
— C0/C20

IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	4W
Current:	0.03A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	90 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	2500K
Lumens:	360 lm
Incandescent equiv.:	33W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	98
TM30 - Rf	90



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 25	Gross weight: 0.31
L 1 4/8 x W 1 4/8 x H 3 7/8in	L 8 2/8 x W 3 3/8 x H 4 3/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights

EAN

5060400151219