

GAIA

6W | 420 lm | 2200K

GAIA-6W-2200K-E26-T-120V

Gaia 6W 2200K E26 Tinted US LED Bulb


tala.

The Gaia bulb by Tala boasts a popular, exposed-filament design that emits a warm, amber light, making it both a functional and attractive light source. Fitted with an E26 base and energy efficient LED technology, the Gaia bulb will last on average 5-10 years based on daily usage.




PHYSICAL

Bulb diameter:	4 7/8in
Bulb length:	6 7/8in
Glass shape:	G40
Base:	E26
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	90g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80
— C0/C270

IES/LDT photometry files and product photography available on request



ELECTRICAL

Power:	6W
Current:	0.05A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	70 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	420 lm
Incandescent equiv.:	37W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 190	Gross weight: 2.3
L 5 1/8 x W 5 1/8 x H 7 4/8in	L 26 3/8 x W 10 7/8 x H 7 7/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060400151332