

OBLO

6W | 540 lm | 2700K

OBLO-6W-2700K-E26-MP-120V

Oblo 6W 2700K E26 Matte Porcelain US LED Bulb


tala

The Oblo bulb by Tala is formed from mouth-blown glass and fitted with energy efficient LED technology, lasting an average of 5-10 years based on daily usage. Oblo illuminates its surroundings and creates a sense of calm and harmony in any context.




PHYSICAL

Bulb diameter:	4 2/8in
Bulb length:	6 4/8in
Glass shape:	T40*
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	170g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



IES/LDT photometry files and product photography available on request



ELECTRICAL

Power:	6W
Current:	0.05A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	90 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	2700K
Lumens:	540 lm
Incandescent equiv.:	45W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	98
TM30 - Rf	92



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 290	Gross weight: 3
L 5 1/8 x W 5 1/8 x H 7 4/8in	L 26 3/8 x W 11 x H 8 2/8in

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060400150298