PRODUCT FEATURES

- Mouth-blown thick organic flowing glass
- · Modern design style
- As each piece is artisan made, slight variations are an inherent part of this hand-blown glass fixture
- Fully dimmable LED and Halogen lamping options to create the desired ambiance
- Ideal for kitchen island task lighting, bathroom lighting and home office lighting
- Protected by a 1-year warranty



LAMPING

Includes low-voltage, 35 watt halogen bi-pin lamp or 6 watt, 300 delivered lumen, replaceable LED Tech Lighting module. Dimmable with low-voltage electronic or magnetic dimmer (based on transformer). Fixture provided with six feet of field-cuttable cable.



ORDERING INFORMATION

| 700 | SYSTEM | ADR | COLOR | FINISH | LAMP |
|-----|-------------------------------------|-----|--------------|----------------|---|
| | TD LINE-VOLTAGE PENDANTS/SUSPENSION | | C CLEAR | S SATIN NICKEL | 12 VOLT HALOGEN (T20) |
| | | | K SMOKE | | -LEDS930 12 VOLT LED 90 CRI 3000K (T20/T24) |
| | | | G SURF GREEN | | |
| | | | W WHITE | | |

Please note. Not compatible with Low-Voltage systems such as Monorail or FreeJack due to weight.

| 700 | ADR | | |
|----------|-----|------|--|
| JOB NAME | | | |
| NOTES | | | |
| | | | |




AUDRA PENDANT

TECH LIGHTING

SPECIFICATIONS

| HARDWARE MATERIAL | Metal | | | |
|-------------------------------|-------------|--|--|--|
| SHADE MATERIAL | Glass | | | |
| NET WEIGHT | 6 lbs | | | |
| HEIGHT | 5.9in | | | |
| WIDTH | 5.3in | | | |
| LENGTH | 5.3in | | | |
| UP LIGHT / DOWN LIGHT / BOTH? | | | | |
| WET LISTED | | | | |
| DAMP LISTED | Yes | | | |
| DRY LISTED | | | | |
| MIN. HANGING HEIGHT | 12.4in | | | |
| MAX HANGING HEIGHT | 78.4in | | | |
| TOTAL CORD LENGTH | 72in | | | |
| TOTAL STEM LENGTH | | | | |
| STEM QTY | | | | |
| SLOPED CEILING ADAPTABLE? | Yes 45° Max | | | |
| GENERAL LISTING | ETL Listed | | | |
| INCLUDES | | | | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|------------|----------------|------------|---------|
| DELIVERED LUMENS | 412.5 | | 450 | |
| WATTS | 6 | | 35 | |
| MAX WATTAGE PER BULB | 35W | | 35W | |
| INPUT VOLTAGE | 120V | | 120V | |
| DIMMING TYPE* | ELV, TRIAC | | ELV, TRIAC | |
| сст | 3000K | | 3000K | |
| CRI | 90 CRI | | 100 CRI | |
| LED LIFETIME | | | | |
| L70 | >30000 | | | |
| AVERAGE BULB HOURS | | | 2000 | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | GY 6.35 | | GY 6.35 | |
| LAMP SHAPE | T4 | | T4 | |
| LAMP INCLUDED? | Υ | | Υ | |
| WARRANTY** | 1 Year | | 1 Year | |

^{*} Dimming information available at www.techlighting.com/Downloads#dimming
** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|-------------------|-------------------------|--------------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6. | | Yes | |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | | Yes | |

^{*}If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

