The contemporary aesthetic of the Blade 24 outdoor wall sconce is sized to match architectural scale as it creates soft indirect, reduced-glare illumination by aiming light back against the wall for accenting architecture as well as for wayfinding. Available in two sizes, 18" and 24" and two finishes.

- Selectable CCT (2700K/3000K)
- Universal 120V-227V
- Outstanding protection against the elements:
 - Wet Listed IP65 Rated
 - Stainless Steel Mounting Hardware
 - Powder Coat Finishes

SPECIFICATIONS


DELIVERED LUMENS	1587
WATTS	28.6
VOLTAGE	Universal 120V-277V
DIMMING	Dimmable with most LED compatible ELV & TRIAC dimmers + 0-10V
LIGHT DISTRIBUTION	Symmetric
OPTICS	not applicable
MOUNTING OPTIONS	Wall
CCT	2700K/3000K Selectable
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B0-U3-G0
DARK SKY	Non Compliant
WET LISTED	IP65
GENERAL LISTING	ETL, ADA
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; >60,000 Hours
WARRANTY*	5 Years
WEIGHT	2 lbs.





ORDERING INFORMATION

PRODUCT	CRI/CCT	LENGTH	FINISH	VOLTAGE
700OWBLD	92730 90 CRI 2700K/3000K SELECTABLE	24 24"	B BLACK 7 BRONZE	UNV 120V–277V



Blade 24 Outdoor Wall

PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES

TECH LIGHTING

Visual Comfort & Co.

© 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400