

K-PIVOT HEAD

PRODUCT FEATURES



LAMPING

Low-voltage, MR16 lamp of up to 75 watts (not included). For Kable Lite system only.

K-Pivot Head



K-Pivot Head

ORDERING INFORMATION

700KPIV	CABLE SEPARATION	FINISH
	01 1.00000	S SATIN NICKEL
	02 2.00000	
	03 3.50000	
	05 5.50000	
	08 8.00000	

700KPIV


JOB NAME

NOTES



K-PIVOT HEAD

SPECIFICATIONS



HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.1 lbs
HEIGHT	2in
WIDTH	1in
LENGTH	1in
BEAM SPREAD	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	
MAX HANGING HEIGHT	
TOTAL CORD LENGTH	
SLOPED CEILING ADAPTABLE?	No
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				75W
INPUT VOLTAGE				12V
DIMMING TYPE*				ELV
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				GU5.3
LAMP SHAPE				BT15
LAMP INCLUDED?				N
WARRANTY**				1 Year

*Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

