

INSTALLATION INSTRUCTIONS

For Model 72116-149

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

HANGING THE FIXTURE (Fig. 1)

1. Shut off the power at the circuit breaker and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.

CONNECTING THE WIRES (Fig.2)

3. While supporting the fixture, connect the electrical wires as shown in figure 2. If your post has a ground wire (green or bare copper), connect the fixture ground wire to it. If not, consult your electrician for proper grounding. After the wires are connected, tuck them carefully inside the post (A).

COMPLETING THE INSTALLATION (Fig. 1)

4. Place the fixture (B) onto post (A), and secure with the mounting screws (C)
5. Remove screws (D) to separate top cover (G) from fixture body (B)
6. Install the bulb (Type B, not supplied) in accordance with the fixture's specification. Attach top cover (G) to fixture body (B) with screws (S).

DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

7. Align top cover (G) to fixture body (B) and secure with screws (D).

Your installation is now complete. Return power to the junction box and test the fixture

Fig. 1




Fig. 2

