
GLOBE PENDANT 50CM





Year of Design 201

Material Polycarbonate, steel and carbon fibre
LED Spec Integrated, serviceable LED, 800 lumens, 3000K,

Cable Spec CRI ≥ 80. 250cm / 98.4in clear cable.

Dimmability Mains dimmable.

Dimmability Mains almmable

Rating/Location IP20





GLOBE PENDANT CHROME 50CM UL

Code GLS02CH-PUSM1 Components GLS02CH LEDP04BKUL

GLOBE PENDANT COPPER 50CM UL

Code GLS02CO-PUSM1 Components GLS02CO LEDP04BKUL

GLOBE PENDANT 50CM

Process

Blow moulded polycarbonate with a semi metallised interior and injection moulded polycarbonate diffuser.

Cleaning Instructions

Clean with a soft dry cloth only.Do not use polishing agents, water or abrasive materials when cleaning. Always switch off the electricity supply before cleaning.

Country of origin Germany

Packaging

GLS02CO
Height 22"
Width 21"
Length 21"
Weight 8.2 lb

LEDP04BKUL

Height 5"
Width 8"
Length 12.5"
Weight 2.9lb

Product weight 5.7lb

Ceiling rose

Polished Chrome Steel Dome 12.5cm/4.9in Ø Polished Copper Steel Dome 12.5cm/4.9in Ø

Requires assembly

Yes


Light Source Included

6W Tom Dixon LED Ring

Voltage

2

220-240V



tomakoi



tomdixon.net