

ASSEMBLY INSTRUCTIONS

Alloway 30" Flush Mount


Item # KS 4230

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver



1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate (B) from canopy (F) by removing screws (E).
3. Install mounting plate (B) to the junction box and secure with mounting screws (C).
4. Connect supply ground wire (usually green or bare copper) around the green grounding screw (see diagram 1). Tighten.

NOTE: It is imperative that the fixture is grounded.

5. Connect fixture neutral wire (black) to driver (D) output wire (black) using wire nut (A).
6. Connect fixture hot wire (red) to driver (D) output wire (red) using wire nut (A).
7. Connect driver (D) input neutral wire (white) to the supply neutral wire (usually white) using wire nut (A).
8. Connect driver (D) input hot wire (black) to the supply hot wire (usually black) using wire nut (A).

CAUTION: Do not reverse the hot and neutral connections.

9. Make sure all wire connections are tight and tuck into the junction box.
10. Insert driver (D) into the bracket of mounting plate (B).
11. Install canopy (F) to mounting plate (B) and secure with screws (E).
12. Thread glass shades (H) to sockets (G).

NOTE: Do not overtighten otherwise shade could become damaged.

Care Instructions: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.