


ASSEMBLY INSTRUCTIONS



Antigua Large Drum Semi-Flush Mount

Item # CHC 4015

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver

Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate (B) from fixture (D) by removing screws (E).
3. Install mounting plate (B) to junction box and secure with mounting screws (C).
4. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire. (usually green or bare copper) using wire nut (A).


NOTE: It is imperative that the fixture is grounded.

5. Connect fixture neutral wires (white) to the supply neutral wire (usually white) using wire nut (A).
6. Connect fixture hot wires (black) to the supply hot wire (usually black) using wire nut (A).

CAUTION: Do not reverse the hot and neutral connections.

7. Make sure all wire connections are tight, then carefully tuck into the junction box.
8. Install fixture (D) to mounting plate (B) and secure with screws (E).
9. Install light bulbs into the sockets.
10. Thread finial (I) to nipple (J). See diagram 2.

ASSEMBLY INSTRUCTIONS



Antigua Large Drum Semi-Flush Mount

Item # CHC 4015

NOTICE:


This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

Diffuser Option:

11. Thread rod (F) to nipple (J).
 12. Attach rubber washers (G) to either side of the diffuser (H) and secure to the rod (F) with finial (G). See diagram 3.
- NOTE:** Do not overtighten otherwise glass could become damaged.

Care Instructions: Clean only with a soft dry cloth or feather duster. Do Not use abrasive or chemical agents.

UNPACKING NOTICE



Antigua Large Drum Semi-Flush Mount

Item # CHC 4015

NOTICE:

Please follow instructions below to avoid possible damages caused by improper removal.

1. Open box and remove top layer of packaging.
2. Gently remove item by evenly lifting from canopy until clear of packaging. Place on clean, soft surface.

NOTE: Remove slowly to avoid damages.

VISUAL COMFORT

