


SL 5870

ASSEMBLY & INSTALLATION GUIDE



WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING * SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

1. Carefully remove all parts carefully from box. Step 2 Hook candelabra assembly (D) onto bottom loop.
2. To install glass panels (C) provided to each frame, make sure metal tab (A) is flipped up. Place four glass panels to each frame, secure the glass panels by bending back the metal tabs (A) downwards.
3. Attach top loop to chain mounting loop by using open end link provided.
4. Feed wire through chain and mounting loop.
5. Slide canopy on chain. Attach mounting strap to ceiling outlet box using proper size screws and tighten securely.
6. Attach nipple into mounting strap and lock into place using included nut.
7. Attach chain mounting loop to thread nipple using screws provided.
8. Attach ground (silver or copper in color) fixture wire to ground wire from ceiling outlet box (usually green or copper in color), and fasten together with a plastic wire connector. Tightly wrap the wire connector with electrical tape so the end of the connector is sealed.

IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUND .

9. Connect the neutral (RIBBED, without any marking) fixture wire to the neutral (usually white) wire from ceiling outlet box. Fasten both wires together with a plastic wire connector and tightly wrap the wire connector with electrical tape.
10. Repeat the procedure with the hot (ROUND, with UL marking on) wire to hot (usually black) outlet wire. Always make sure that no wire strands are left outside of the connections.

DO NOT REVERSE THE HOT AND NEU1RAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.

11. Tuck wire connection neatly into ceiling outlet box.
12. Slip canopy to ceiling and secure with threaded canopy ring. Insert light bulb into the socket.