

SL2702

ASSEMBLY & INSTALLATION GUIDE

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

1. Place base plate (C) on wall at desired height. Use a level to make sure the base plate (C) is vertical.
2. Using a pencil, make a mark in the top center of each keyhole.
3. Drill 1/8" holes into your pencil marks on the wall. For each hole:
 - If you encounter a wall stud, then drive a mounting screw (B) into the hole with a Phillips screwdriver.
 - If you don't encounter a wall stud, drive a metal anchor (A) into the hole using a Phillips screwdriver. Once the metal anchor (A) is flush with the wall surface, drive a mounting screw (B) into the metal anchor (A) using a Phillips screwdriver.
 - In both cases, leave approximately 1/8" of screw threads exposed.
4. Hook base plate (C) onto mounting screws (B). If the base plate (C) are not snug against the wall, remove it, tighten each screw 1/4 turn, and replace the base plate (C). Repeat until snug.
5. Install bulb of correct type and wattage. See label on lamp.
6. Remove protective plastic (F) from electrical plug (E).
7. Plug lamp into wall outlet.
8. ADJUSTMENT INSTRUCTIONS:
 1. Loosen adjustment keys (D).
 2. Adjust lamp arm and lamp shade to desired height and position.
 3. Tighten the adjustment keys (D).

