## NATE 9 OUTDOOR WALL

## PRODUCT FEATURES

- Powerful, long lasting (L70, 70,000 hours) dimmable LED tested against the highest quality standards to ensure it delivers consistent LED performance and color over time.
- Die-cast aluminum structure, powder coat finish and stainless steel hardware for robust durability in harsh elements.
- Wet listed, IP65 (International Protection rating indicating resistance to dust and water).
- 5- year Warranty. Go to www.techlighting.com for warranty details.
- · Available in modern finishes

#### LAMPING



Black



### ORDERING INFORMATION

7000WNTE	LENGTH (A)	FINISH	LAMP
	9 9"	B BLACK	-LED930 LED 90 CRI 3000K 120V
		Z BRONZE	
		I SILVER	


7000WNTE	
JOB NAME	
NOTES	



# NATE 9 OUTDOOR WALL

## **SPECIFICATIONS**

PRIMARY MATERIAL	Aluminum
SHADE MATERIAL	Aluminum
NET WEIGHT	2 lbs
HEIGHT	9.lin
WIDTH	4in
LENGTH	5.5in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



### LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		38.1		
WATTS		5.9		
MAX WATTAGE PER BULB				
		120V ELV		
ССТ		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>60000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

<sup>\*</sup>Dimming information available at <u>www.techlighting.com/Downloads#dimming</u>

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6/JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

 $<sup>^{\</sup>star}$  If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup> Visit techlighting.com for specific warranty limitations and details.