

# PONTE LARGE LINEAR CHANDELIER

VISUAL COMFORT & CO.

## PRODUCT FEATURES



## LAMPING

Includes 31.4 watts, 1436 total delivered lumens, 3000K LED modules.  
Dimmable with most LED compatible ELV, TRIAC and 0-10V dimmers.  
Ships with (4) 12" and (2) 6" rigid stems in coordinating finish. 120V-277V.

## ORDERING INFORMATION

| SLLS571 | COLOR TEMP | FINISH                        |
|---------|------------|-------------------------------|
|         | 303000K    | HAB HAND RUBBED ANTIQUE BRASS |
|         |            | B NIGHTSHADE BLACK            |

SLLS571 \_\_\_\_\_

JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_



## SPECIFICATIONS

|                               |                   |
|-------------------------------|-------------------|
| PRIMARY MATERIAL              | Aluminum or Brass |
| SHADE MATERIAL                | Aluminum or Brass |
| NET WEIGHT                    | 5 lbs             |
| HEIGHT                        | 5.2in             |
| WIDTH                         | 1.5in             |
| LENGTH                        | 50in              |
| UP LIGHT / DOWN LIGHT / BOTH? |                   |
| WET LISTED                    |                   |
| DAMP LISTED                   |                   |
| DRY LISTED                    |                   |
| MIN. HANGING HEIGHT           | 15.8in            |
| MAX HANGING HEIGHT            | 77.3in            |
| TOTAL CORD LENGTH             |                   |
| TOTAL STEM LENGTH             | Up to 60in        |
| STEM QTY                      | 6                 |
| SLOPED CEILING ADAPTABLE?     | Yes 22.5° Max     |
| GENERAL LISTING               | ETL Listed        |
| INCLUDES                      |                   |

## LAMPING SPECIFICATIONS

|                       | LED LAMP | INTEGRATED LED                       | NON LED | NO LAMP |
|-----------------------|----------|--------------------------------------|---------|---------|
| DELIVERED LUMENS      |          | 1436                                 |         |         |
| WATTS                 |          | 31.4                                 |         |         |
| MAX WATTAGE PER BULB  |          | 31.4W                                |         |         |
|                       |          | Universal 120V-277V 0-10, ELV, TRIAC |         |         |
| CCT                   |          | 3000K                                |         |         |
| CRI                   |          | 90 CRI                               |         |         |
| LED LIFETIME          |          | >50000                               |         |         |
| L70                   |          |                                      |         |         |
| AVERAGE BULB HOURS    |          |                                      |         |         |
| FIELD SERVICEABLE LED |          |                                      |         |         |
| LAMP BASE             |          | Integrated LED                       |         |         |
| LAMP SHAPE            |          | Integrated LED                       |         |         |
| LAMP INCLUDED?        |          | True                                 |         |         |
| WARRANTY**            |          | 5 Years                              |         |         |

\* Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)

\*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

|   | Integrated LED | Replacement LED Lamp | No Lamp * |
|---|----------------|----------------------|-----------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.                           | Yes            |                      |           |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. |                |                      |           |

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

