

## ASSEMBLY INSTRUCTIONS

## Rigby Medium Bridge Arm Floor Lamp

Item # MF1055

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

### TOOLS REQUIRED (NOT INCLUDED):

Scissors

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Let rod (F) and loader (H) pass through base (G), then secure with washer (I) and hex nut (J) using provided wrench (K).
3. Remove adhesive backing from felt pad (L), and neatly apply to bottom of base (G).
4. Remove shade (C) from packaging, then install metal rings (B & D) to the top and bottom of shade (C) and secure by bending metal tabs (N). See diagram 1.
- NOTE:** If shade has additional packaging, carefully cut off from interior of shade to avoid damages.
5. Remove socket ring (A) from socket (E), then install shade (C) to socket (E) and secure with socket ring (A).
6. Remove protective cover (M) from the plug.
7. Plug into electrical outlet and test the fixture.

**Care Instructions:** Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.

