


# TUBE ARCHITECTURAL DS-CD05

# WAC LIGHTING

## LED Ceiling Mounts



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

### FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle or glare control
- 5 year warranty

### SPECIFICATIONS

**Input:** Universal voltage 120V - 277VAC, 50/60Hz  
**Dimming:** Electronic low voltage (ELV) : 100% - 5%  
 0-10V: 100% - 1%  
**Light Source:** High output 3 Step Mac Adam Ellipse COB  
 Rated life of 60,000 hours at L70  
**Finish:** Electrostatically powder coated, white, black, bronze and graphite  
**Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.2 rated Title 24 JA8-2016 Compliant  
**Operating Temp:** -13°F to 122°F (-25°C to 50°C)

### ORDERING NUMBER

| Diameter  | Watt | Beam        | Angle | Color | Temp  | CRI | Reference Lumens | Output <sup>1</sup> CBCP | Efficacy (Lm/W) | Light Distribution | Finish   |
|-----------|------|-------------|-------|-------|-------|-----|------------------|--------------------------|-----------------|--------------------|--|
| DS-CD05   | 25W  | S<br>Spot   | 16°   | 927   | 2700K | 90  | 1825             | 10050                    | 73              |                    | BK Black<br>WT White<br>BZ Bronze<br>GH Graphite |
|           |      |             |       | 27    | 2700K | 85  | 2190             | 12057                    | 88              |                    |  |
|           |      |             |       | 930   | 3000K | 90  | 1895             | 10427                    | 76              |                    |  |
|           |      |             |       | 30    | 3000K | 85  | 2300             | 12644                    | 92              |                    |  |
|           |      |             |       | 35    | 3500K | 85  | 2350             | 12937                    | 94              |                    |  |
|           |      |             |       | 40    | 4000K | 85  | 2375             | 13062                    | 95              |                    |  |
| DS-CD0517 | 17W  | N<br>Narrow | 25°   | 927   | 2700K | 90  | 1810             | 5280                     | 72              |                    | BK Black<br>WT White<br>BZ Bronze<br>GH Graphite |
|           |      |             |       | 27    | 2700K | 85  | 2170             | 6335                     | 87              |                    |  |
|           |      |             |       | 930   | 3000K | 90  | 1880             | 5478                     | 75              |                    |  |
|           |      |             |       | 30    | 3000K | 85  | 2275             | 6643                     | 91              |                    |  |
|           |      |             |       | 35    | 3500K | 85  | 2330             | 6797                     | 93              |                    |  |
|           |      |             |       | 40    | 4000K | 85  | 2350             | 6863                     | 94              |                    |  |
|           |      | F<br>Flood  | 33°   | 927   | 2700K | 90  | 1900             | 4515                     | 76              |                    | BK Black<br>WT White<br>BZ Bronze<br>GH Graphite |
|           |      |             |       | 27    | 2700K | 85  | 2280             | 5417                     | 91              |                    |  |
|           |      |             |       | 930   | 3000K | 90  | 1970             | 4685                     | 79              |                    |  |
|           |      |             |       | 30    | 3000K | 85  | 2390             | 5681                     | 96              |                    |  |
|           |      |             |       | 35    | 3500K | 85  | 2445             | 5812                     | 98              |                    |  |
|           |      |             |       | 40    | 4000K | 85  | 2470             | 5870                     | 99              |                    |  |

DS-CD05- \_\_\_\_\_ - \_\_\_\_\_

<sup>1</sup>Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

Example: DS-CD05-N927-BK

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760