




Basic geometry

	XS	S	M	L	XL
Body Height in cm	≤ 166	166 - 175	175 - 183	183 - 192	≥ 192
Seat Height in mm (a)	618 - 763	648 - 843	673 - 868	703 - 898	733 - 928
Seat Tube Length in mm (b)	415	420	420	450	480
Top Tube Length in mm (c)	559	585	609	633	656
Head Tube Length in mm (d)	90	90	100	115	130
Head Tube Angle (e)	67°	67°	67°	67°	67°
Seat Tube Angle (f)	76°	76°	76°	76°	76°
Chainstay Length in mm (g)	435	435	435	435	435
Wheel Base in mm (h)	1.129	1.155	1.180	1.206	1.232
Stack in mm (i)	589	589	598	612	626
Reach in mm (j)	412	438	460	480	500
Stand-over Height in mm (k)	768	768	772	777	783
Bottom Bracket Offset in mm (l)	38	38	38	38	38

Component geometry

	XS	S	M	L	XL
Spacer in mm	20,0	20,0	20,0	20,0	20,0
Stem Length in mm	50	50	50	50	50
Handlebar Width in mm	760	760	760	760	760
Crank Length in mm	170,0	170,0	175,0	175,0	175,0
Chainring Size	32	32	32	32	32
Seat Post Diameter in mm	31,6	31,6	31,6	31,6	31,6
Dropper post travel in mm	100	125	150	150	150
Seat Post Length in mm	380	455	480	480	480
Maximum Seat Post Insertion Depth in mm	225	275	275	275	275
Minimum Seat Post Insertion Depth in mm	80	80	80	80	80
Wheel Size	29"	29"	29"	29"	29"
Disc Size in mm	180 / 160	180 / 160	180 / 160	180 / 160	180 / 160
Front Fork Travel in mm	120	120	120	120	120
Rear Suspension Travel in mm	115	115	115	115	115
Fitting Length	210X50	210X50	210X50	210X50	210X50