Air Cleaner Test Report

Applicant : RHT Industries Limited

Address : Block B, 2/F, Goodwill Industrial Building, No. 36-44 Pak Tin Par

Street, Tsuen Wan, New Territories, Hong Kong

Application Number : KJ191001-09

Report Number : REPAP19111701

Report Issue Date : 20 Nov 2019

Total Page : 9 Pages (including this page)

This document is issued by the Company under its General Conditions of Service printed overleaf. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any older of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30days only. This document cannot be reproduced except in full, without prior approval of the Company.

TABLE OF CONTENT

1.	Sample Description	3	
2.	Detail Description of the sample	4 - 5	
3.	Testing Environment	6	
4.	Testing Method of Removal Efficiency	7	
5.	Result of Removal Efficiency	8 – 9	

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program

Page 2 of 9

1. Sample Description

Product : Air Cleaner

Brand Name : b-MOLA

Model No. : MOLA300

No. of Sample Received : 1

Test Date : 13 Nov 2019 – 13 Nov 2019

Test Item(s) : Pollutants Removal Efficiency

Test Requested : Acetic Acid

Test Reference(s) : In-house method SOP200 (for VOC removal rate)

Test Equipment : Honeywell instrument ppbRAE 3000

Equipment no. : E002 - 002

Test Result : See the attached sheets

Remark : Client claimed that model MOLA300 same as IA60/BM300 in

terms of power, parts, components and structures. Only

different is the selling platform.

2. Detail Description of the sample





b-MOLA/MOLA300

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program

Page 4 of 9



NCCO Reactor (NA213020300) and Activated Carbon HEPA

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program

Page 5 of 9

3. Testing Environment

Temperature : 25 °C

Relative Humidity : 49 %

Testing Chamber : 3m³ Testing Chamber

Size $(W \times H \times D)$: $1.40m \times 1.40m \times 1.50m$



3m³ Testing Chamber

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program

Acron International Technology Limited
Your Technical Companion
HKUST Entrepreneur

4. Testing Method of Removal Efficiency

In a 3m^3 chamber, chemical was injected into the chamber by a syringe and evaporated by a hot plate. Internal circulation was turned on throughout the test to ensure the uniformity of chemical concentration inside the chamber. Initial concentration (C_0) of the chemical was recorded before switching on the air cleaner with a range of $100 \ (\pm 10) \ \text{mg/m}^3$. Then, the air cleaner is switched on for 60 minutes and the chemical concentration was recorded as C_{60} , the final concentration of chemical.

The test was repeated without the air cleaner to determine the natural decay of the chemical at the test chamber. Chemical was injected into the chamber by a syringe and evaporated by a hot plate with an initial concentration (C_{N0}). The final concentration (C_{N60}) was determined 60 minutes later

New filters and HEPA have been used for each chemical test.

5. Results of Removal Efficiency

Brand/ Model No.	Operation Mode	Test Chemical	Volume
			(mL)
b-MOLA/MOLA300	SS	Acetic Acid	0.80

Initial Concentration	Natural Decay, kn	Total Decay, ke	Removal Efficiency	
(mg/m^3)	(min ⁻¹)	(min ⁻¹)	(%)	
95.19	0.002	0.024	96	

Remark: Initial concentration is set within 100±10mg/m³.




Figure a. Natural Decay of Acetic Acid

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program






Figure b. Total Decay of Acetic Acid

Calculation:

$$A_{1} = \cfrac{C_{0} - C_{60}}{C_{0}}$$

$$A_{2} = \cfrac{C_{N0} - C_{N60}}{C_{N0}}$$

$$C_{0}(1 - A_{2}) - C_{60}$$
 Removal Efficiency =
$$\cfrac{C_{0}(1 - A_{2})}{C_{0}(1 - A_{2})}$$

 A_1 : Removal rate (%)

A₂: Natural decay rate (%)

C: Concentration of testing subject (mg/m³)

End of Report

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program