Air Cleaner Test Report

Applicant : RHT Industries Limited

Address : Block B, 2/F, Goodwill Industrial Building, No. 36-44 Pak Tin Par

Street, Tsuen Wan, New Territories, Hong Kong

Report Number : REPAP19041801

Report Issue Date : 18 Apr 2019

Total Page : 6 Pages (including this page)

This document is issued by the Company under its General Conditions of Service printed overleaf. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any older of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30days only. This document cannot be reproduced except in full, without prior approval of the Company.

1. Sample Description

Product : Air Cleaner

Brand Name : b-MOLA

Model No. : NCCO1701

No. of Sample Received : 1

Test Date : 27 Mar 2019 – 27 Mar 2019

Test Item(s) : Pollutants Removal Efficiency

Test Reference(s) : In-house method SOP200 (for VOC removal rate)

Test Result : See the attached sheets

Remark : N/A

Report No.: REPAP19041801

2. Detail Description of the sample





b-MOLA/NCCO1701

Acron International Technology Limited

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program



NCCO Filter and HEPA

IAQ Contractor, IAQ Control Facilities Supplier, IAQ Consultant Subsidiary company of the Hong Kong University of Science and Technology under the Entrepreneurship Program

3. Results of Removal Efficiency for Chemical Pollutant

Brand / Model No.	Operating	Test Chemical	Initial	Removal
	Mode		Concentration	Efficiency (%)
b-MOLA/NCCO1701	SS	Acetic Acid	100.7 ppm	>99.9

Remark: Initial concentration is set within 100±10ppm.

In a 1m^3 chamber, chemical was injected into the chamber by a syringe and evaporated by a hot plate. Internal circulation was turned on throughout the test to ensure the uniformity of chemical concentration inside the chamber. Initial concentration (C_0) of the chemical was recorded before switching on the air cleaner with a range of 100 (± 10) ppm. Then, the air cleaner is switched on for 60 minutes and the chemical concentration was recorded as C_{60} , the final concentration of chemical.

The test was repeated again without the air cleaner to determine the natural decay of the chemical at the test chamber. Chemical was injected into the chamber by a syringe and evaporated by a hot plate with an initial concentration (C_{N0}). The final concentration (C_{N60}) was determined 60 minutes later

New filters and HEPA have been used for each chemical test.

Report No.: REPAP19041801

Calculation:

$$A_1 = \cfrac{ \cfrac{C_0 - C_{60}}{C_0} }{ \cfrac{C_{N0} - C_{N60}}{C_{N0}} }$$

$$A_2 = \cfrac{ \cfrac{C_{N0} - C_{N60}}{C_{N0}} }{ \cfrac{C_{N0} - C_{N60}}{C_{N0}} }$$

Removal Efficiency =
$$\frac{C_0(1 - A_2) - C_{60}}{C_0(1 - A_2)}$$

End of Report