

Version 0.5 Date: 08.04.2024 Revision date: Page 1 of 4

1 <u>Company</u>

Manufacturer/Supplier:Konica Minolta Business Solutions Europe GmbHTel.:+49/511/7404-0Address:D-30855 Langenhagen, Europaallee 17Fax:+49/511/741050

Before getting back to the editor, please contact your local support first

Editor: Konica Minolta, Sustainability Management, ESG Tel.:+49/511/7404-361

Markus Kelch Fax:+49/511/7404-396

ISO 14001.

markus.kelch@konicaminolta.eu

2	Tests / Approvals / Declarations			
2.1	CE Conformity:	Declaration of Conformity	For this product an EU Declaration of Conformity according to EN17050-1 is available. It can be obtained from the editor on request.	
2.2	EU-Directives:		This product is in compliance with the listed EU directives: - Low Voltage Directive / Product Safety - EMC Directive / Electromagnetic Compatibility - ErP Directive / Eco Design - RoHS2 Directive and amendments	
		2014/35/EU 2014/30/EU 2009/125/EC 2011/65/EC		
2.3	Safety Tests:	Nemko Mark P 232 273 92	NEMKO, Norway	EN 62368-1
2.4	EAC Certification:	KG 417/026.JP.02.11558 (0136831)	EAC certificate	
2.5	Electromagnetic Compatibility (EMC):	EMC Mark	NEMKO, Norway	EN 55032, EN 55024, EN 61000-3-2, EN 61000-3-3
2.6	ENERGY STAR:	ENERGY STAR program compliance	EPA based (version 3.2)	This product is listed in ENERGY STAR databases
2.7	Eco Design Directive:	2009/125/EC 1275/2008/EC	Framework for the setting of eco design requirements for energy-related products Requirements for electrical power consumption in standby and off-mode	
2.8	Blue Angel Mark:	German environmental label is applied	RAL	DE-UZ 219
2.9	Document Authenticity:	PTS certificate will be applied Printer: Copier: ISO 11798 will be applied	Papiertechnische Stiftung (PTS) RISE (Sweden)	Ordinance for Lawyers and Notaries in Germany (DONot), § 29; According Swedish National Archive Regulations relevant test conditions were noted down in the according test certificate!
2.10	Laser safety	EN 60825-1 : 2014	Class 1 laser	
2.11	Quality and Environmental Management:	ISO 9001 certification ISO 14001 certification	This product was manufactured under a certified Quality Management System according to ISO 9001 and under a certified Environmental Management System according to	



Version 0.5 Date: 08.04.2024 Revision date: Page 2 of 4

General Information Pages per minute 3.1 Speed: Black and White Colour Printing 55 (ISO 24734) 55 (ISO 24735) Copying Basic System only 3.2 Weight: About 98 kg Dimensions / Volume: 3.3 615 mm Width Basic System only 688 mm Depth 961 mm Height 407 litre Volume (calculated) 3.4 This product conforms to the Konica Minolta Environmental Policy Environmental programmes: following voluntary environmental Konica Minolta Product Environmental Assessment programme requirements: All production sites have ISO 14001 certification. Konica Minolta Environmental Report including environmental accounting report is published annually. https://www.konicaminolta.com/about/csr/environment/index.html Extension of product lifetime: The manufacturer offers on a Spare parts availability: 7 years after end of production voluntary base: Service availability: 7 years after end of production (depends on service level agreement, business to business) Warranty: Depends on service level agreement, business to business Cadmium (< 0.01%) Materials: This product contains no*: Lead Hexavalent chromium Mercury (except for a fluorescent lamp) PBB and PBDE (Polybrominated biphenyls and their ethers contained in mechanical plastic parts in concentrations exceeding the natural background levels) Ozone depletion substances, according to those categories that are already banned in the Montreal protocol Chloroparaffines with chain length 10-13 atoms, chlorination greater than 50% contained in mechanical plastic parts PCB or PCT Large-size plastic case parts (weighing more than 25g) do not contain the halogenated flame proofing agents. Asbestos * Impurity threshold level: less than 0.1%

4 Emissions / Consumption

4.1 Operation noise:

(Measured values) Sound power, Lwa ¹⁾

Sound power declared, Lwad

Sound pressure, operator position, Lpa ²⁾

Black and White				
Standby	x.xx dB(A)			
Printing	66.7 dB(A)			
Standby	x.xx dB(A)			
Printing	69.7 dB(A)			
Standby	x.xx dB(A)			
Printing	x.xx dB(A)			

Colour				
Standby	dB(A)			
Printing	dB(A)			
Standby	dB(A)			
Printing	dB(A)			
Standby	dB(A)			
Printing	dB(A)			

Basic unit without accessories

1) measured and declared according to ISO7779, DE-UZ 219

 workspace related emission value, operator test position: height=1.50m; distance=0.25m in front of the panel position

nm Not measured

nd There is no noise in ready mode two minutes after the last printout



Version 0.5 Date: 08.04.2024 Revision date: Page 3 of 4

Emissions / Consumption 4.2 Power [Watt] Mode (230V) Energy (measured values) Max power consumption 3) Max. 2000 Starting Printing Average power consumption 4) 780 Operating Standby 76 Without energy-save 32.8 With energy-save 0.4 Sleep mode 0.028 Plug-in off mode Recovery times Time [seconds] Recovery from mode Energy-save mode 2 3 Sleep mode Applied standard test method: DE-UZ 219 Short-term maximum value, for mains fuse calculation Calculation basis for power consumption TEC Version 3.2: 0.74 kWh/week Typical Energy Consumption Only for reference: value, weekly base, according Version 2.0: x.x kWh/week to the definitions of ENERGY STAR (230V) **Heat Generation** Printing 2,808 kJ/h (calculated) BTU 230V, based on the TEC value of BTU/h this product (24 h x 7 days) Standby 274 kJ/h Without energy-save 4.3 **Emissions:** Substances Operation Emission rate Concentration 5) (Measured values) (Printing) [mg/h] [mg/m³]Ozone Standby nm Operating b/w 0.180 mg/h 0.009 mg/m³ Styrene Standby nm Operating b/w 0.107 mg/h 0.005 mg/m³ Benzene Standby Nm <0.00<u>1 mg/m³</u> Operating b/w 0.001 mg/h TVOC Standby 0.061 mg/h 0.003 mg/m³ 0.103 mg/m^3 Operating b/w 2.061 mg/h Fine dust Standby nm 0.660 mg/h 0.033 mg/m³ Operating b/w Test conditions according to DE-UZ 219. Emission rate in mg/h. **Test conditions** Basic system without options / accessories 5) - Calculation to evaluate the ambient air concentration rate in mg/m³: Room size 40 m³, Air exchange rate 0.5/h, and Multi operating cycles. nd = not detectable (below the detection limit) nm = not measured Regular maintenance assumed. Measured values were evaluated on basis of one machine. Values many vary within production.



Version 0.5 Date: 08.04.2024 Revision date: Page 4 of 4

5	Consumables and other items				
5.1	Toner:	black, for bizhub 451i, bizhub 551i, bizhub 651i (TN628)	Components: Styrene acrylic resin, polyester resin, ferrite (iron oxide and manganese oxide), carbon black, wax, amorphous silica, organic pigment (<1%). Flashpoint over 350 °C. When used as intended (toner for office copies) no danger for health and environment. Avoid dusting. Test on mutagenic activity (AMES) showed negative results. Classification class for endangerment of water: WGK = 1 (Germany, slightly endangering water) Waste toner classification no. (EWC): 080318, GC020, green list, not hazardous waste Polymerized toner reduces environmental impacts (CO2, NOx and SOx emissions during production of toner) by about 40% compared to conventional toners.		
5.2	Waste toner box:	1 box	Must be replaced after 300,000 printouts		
5.3	Photoconductor:	Photoconductor for: bizhub 451i, bizhub 551i, bizhub 651i	Aluminium tube coated with organic material.		
5.4	Filters:	This product contains 1 filter	Must be replaced after 330,000 printouts		
5.5	Batteries:	1 lithium battery (CR2032)	The batteries are in conformity with 2006/66/EC (battery and accumulators). The product documentation contains information about proper disposal, which should be followed		
5.6	Light source:	Scanner lamp	LED		
5.7	Recycling paper	Papers according to EN 12281:2002 are suitable for use	Storage in climate-proof packaging recommended		
5.8	Packaging material:	Material Paper / Cardboard Plastic Foamed PE Plastic PE Others	Weight [kg] x.xx x.xx x.xx x.xx		
		Packaging material is free of PVC			
5.9	Disassembly/Recycling:	Mechanical plastic parts weighing more than 25g are marked according to ISO 11469. Of total plastic parts' weight >25g, recycled material content percentage is 39.35% according DE-UZ 219.			
5.10	Take back information:	The supplier offers take back and recycling services for products and consumables in many locations throughout the world. Customers are advised to contact their supplier representatives for additional information.			
5.11	Documentation:	The documentation is available as printout on Totally Chlorine Free bleached paper or as electronic file. https://manuals.konicaminolta.eu/konicaminolta			
		x.xx means: data not yet available.	x.xx means: data not yet available.		