

Polyurethane Cleaner

DESCRIPTION

TamPur Cleaner is a mixture of non-volatile, chloride-free, non-toxic organic solvents for cleaning up equipment when using the Normet Polyurethane.

KEY BENEFITS

- › Non-flammable.
- › Chloride-free.
- › Non-hazardous solvent.
- › Low evaporation meaning less discomfort to the work force.

TYPICAL APPLICATIONS

- › To clean equipment used with the TamPur range.
- › To clean substrates from overflow or spills.
- › As a flushing liquid to prepare injection pumps.

TECHNICAL DATA

TamPur Cleaner	
Appearance	Clear to yellowish liquid
Density @ 20°C	1.200 g/cm ³
Viscosity @ 20°C	2.76 mPa.s
Freezing Point	-49 °C
Flash Point	116 °C
Toxic	No

All technical data stated herein is based on tests carried out under laboratory conditions.

APPLICATION GUIDELINES

Pumps should be thoroughly primed with TamPur Cleaner to lubricate and dry the system before injection. The cleaner must be removed prior to charging with resin.

When the injection is complete, clean all tools and pumps which have been in contact with the resin, with TamPur Cleaner. This should be done before the resin has hardened.

The pumps should be cleaned by re-circulation for at least 2 minutes and the cleaner should then be replaced with fresh cleaner and the process repeated.

Product and residue should be disposed of according to local legislation. Refer to the product Safety Data Sheet for general recommendations.

In case of spills and accidents, refer to the Safety Data Sheet of the product or when in doubt contact your local Normet representative directly.

Always wear appropriate protective wear for the job at hand according to local guidelines and regulations.

PACKAGING

TamPur Cleaner 20 kg drums. Packaging size may vary subject to local regulations and requirements.

STORAGE

TamPur Cleaner should be stored out of direct sunlight, at room temperature (min 10°C, max 38°C) and kept dry. If these conditions are maintained and the product packaging is unopened, then a shelf life of two years can be expected.

HEALTH & SAFETY

TamPur Cleaner should only be used as directed. We always recommend that the Safety Data Sheet (SDS) is carefully read prior to application of the material. Our recommendations for protective equipment should be strictly adhered to for your personal protection. The Safety Data Sheet is available upon request from your local Normet representative.

Whilst any information and/or specification contained herein is to the best of our knowledge, true and accurate, we always recommend that a trial be carried out to confirm suitability of the product. Please note regional climatic conditions may cause a variation in the performance of the product. No warranty is given or implied in connection with any recommendations or suggestions made by us or our representatives, agents or distributors. The information in this data sheet is effective from the date shown and supersedes all previous data. Please check with your local Normet office to confirm that this is current issue.