

Walkin' Wheels MINI Front Wheel Attachment Assembly Instructions

The Walkin' Wheels Front Wheel Attachment gives mobility to dogs with front leg weakness or weakness in all four legs. It is ideal for helping disabled pets get exercise and for rehabilitation while they are healing. Like the rest of the Walkin' Wheels products, the Front Wheel Attachment is adjustable, so it will fit the Walkin' Wheels wheelchair for any size dog from 2 to 10 pounds and can easily be removed at any time.

Note: Your dog's fold of flank rear leg measurement determined the Front Wheel Attachment size you received.

What's in the B2 or B3 Front Box:




Set-up for Rear Mini Walkin' Wheels

(This must be done first)

1. Remove the rear clamps, leg rings, and front harness.
2. Remove adjustment knob and small washer from the knuckle.
3. Pull out the strut/wheel assembly.
4. Remove both sides of the black round knuckle.
5. Remove the two side extenders and rotate them so that the square hole is now attached to the knuckle on each side. (Make sure the line indicators on the side extenders still face outward on each side.) (See illustration below)

Please watch instructional video here: hpets.net/mfwa

6. Insert the bolt through the middle square hole on the frame and through the side extender square hole.
7. Reinstall the knuckle by placing half of it over the bolt.
Make sure the arrow is pointing to front of the wheelchair, teeth on the outside.
8. Attach outside half of knuckle making sure the arrow is pointing upwards, teeth on inside.
9. Insert strut in knuckle at correct height for your dog.
10. Replace washer and adjustment knob and tighten.




Installing the Front Wheels on to the Frame

(see Diagram 1)


Note: You won't be using the front harness that came with the rear wheelchair.

On top of the caster wheels you will see the letter "R" or "L;" the "R" is for the dog's right leg, and the "L" is for the dog's left leg.

Diagram 1 (for B2 or B3)



1. Remove the adjustment knob on the knuckle, holding the bonded knuckle together in one piece, remove bolt and washer. Attach knuckle to the center of the slot on the side extender. Keeping the knuckle together in one piece, should insure the correct angle for caster mount and wheel.
(caster mount should always be parallel to ground).
2. Insert bolt through side extender, put on flat washer, then adjustment knob, screw on tightly.
3. Do the same for the other front wheel. **If you have the B1, continue to step 5.**
4. Connect both the right and left sides of the front stabilization bar. Make sure that both sides are aligned, insert bolt through square hole (bolt should sit flush against bar), put on flat washer then lock washer, attach adjustment knob and screw on tightly (the center of the stabilization bar should not move). Some movement of the stabilization bar at the caster mount screws is normal.
5. Attach the front and rear leg rings by threading the leg ring wire down through each of the leg ring clamp channels, and then wrapping the wire up and around the frame. Front leg rings should hang slightly lower than rear leg rings to accommodate the chest. (See image below)



WIDTH: Adjust the width in the back from your pet's widest body part (usually the chest). There are several square holes to select from.

- Make sure the knobs are tightened and secure.

WIDTH: Adjust the height so that the side extender frame is positioned in the middle of your pet's body.

- The paws should just be touching the ground
- Knobs should be tightened to secure the strut to the frame.
- The leg rings should hang down about 3" below the blue frame like a seat, with the connector piece holding the two soft tubes together. Front leg ring will be slightly lower than the rear one.

LENGTH: Adjust the length by loosening the knob on the front knuckle and sliding the knuckle to the correct position. Each leg ring wire will be close to the black knuckle on each side.

- Your pet's front legs will be lined up with the black knuckles in the front and rear.

STIRRUPS: If your dog's rear legs are paralyzed, you will need to use the stirrups to hold the feet up so they don't drag on the ground.

- Secure the end with the knot over the adjustable knob and tighten with the push button to hold it tightly. (see Diagram 2, above)

If you are still unsure about the fit, please email rear and side view photographs of your pet in the wheelchair to: helpme@walkinpets.com. Remember to put your order number in the subject line!

In the BF1 Package

The Front Wheel Attachment is easy to assemble. You won't need any tools.

The package contains:




Diagram 3 (for B1)

