



## UEES.E210160 Visual-signal Appliances

---

### Visual-signal Appliances

See General Information for Visual-signal Appliances

**TOMAR ELECTRONICS INC**

E210160

2100 W OBISPO AVE  
GILBERT, AZ 85233 USA

**Flashing warning light and beacons**, Model(s) 470SSGP-120(b)(i11)(i3), 801BL-1224-AC/DC(c)(i3)(i11), 801BL-1224-L (c) (i3) (i11),, 801BLP-1224-L(c) (i3) (i11).

**Flashing warning lights**, Model(s) \*270LF(X)(i11)(e), \*290LF(X)(i11)(e), \*295LF(X)(i11)(e), 550-1228(c)(i11)(i3), 550PMB-1228(c)(i11)(i3), 550PMBX-1228(c)(i11)(i3).

**Steadyburn warning lights**, Model(s) \*270LS(X)(i11)(d), \*290LS(X)(i11)(d), \*295LS(X)(i11)(d).

**Strobe lights**, Model(s) 470SSGP-120/T(b)(i11)(i3), 480S-120(b)(i11)(i3), 480S-120/T(b)(i11)(i3), 480SMB-120(b)(i11)(i3), 480SMB-120/T(b)(i11)(i3), 485S-120(b)(i11)(i3), 485S-120/T(b)(i11)(i3), 485S-240(b)(i11)(i3), 490S-120(b)(i11)(i3), 490S-120/T(b)(i11)(i3), 490S-240(b)(i11)(i3), 492S-120(b)(i11)(i3), 492S-120/T(b)(i11)(i3), 495S-120(b)(i11)(i3), 495S-120/T(b)(i11)(i3), 495S-240(b)(i11)(i3), 801(a)(i3), 8024(a)(i3), 804(a)(i3), 824(a)(i3).

(a) - Rated 120 Vac or 240 Vac, 50/60 hz.

(b) - Rated 120 Vac, 50/60 hz.

(c) - May be followed by amber, blue, green, clear, purple or red.

(d) - May be followed by -120-240 or -12-80, may be followed by amber, blue, green, white and red. (X) Optional: denoting B for black cap or C for clear cap. Beacon Lights are rated 4X. Intended for indoor or outdoor use.

(e) - May be followed by -120-240 or -12-80, may be followed by amber, blue, green, white and red. (X) Optional: denoting B for black cap or C for clear cap. Flashing Lights are rated 4X. Intended for indoor or outdoor use.

(i11) - Type 4X enclosure rating.

(i3) - Indoor or outdoor use.

\* - Also Listed as a Marine Visual Signal Device, UXUB.

Last Updated on 2008-10-28

---