



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : SCHRADER - VULCANISING FLUID "QUARTZ"  
 Product code : 66315/66316(EN).  
 66317  
 - Code 9336; #171 - Code 9335.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

For tubes cold cure repair.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : SCHRADER sas.  
 Address : BP 29 - 48 rue de Salins.25301.Pontarlier Cedex.France.  
 Telephone : +33 (0)3 81 38 56 56. Fax : +33 (0)3 81 46 41 42.  
 Email : resale.info@schrader.fr  
 http://www.schrader.fr

#### 1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).  
 Acute oral toxicity, Category 4 (Acute Tox. 4, H302).  
 Skin sensitisation, Category 1 (Skin Sens. 1, H317).  
 Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

##### In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Highly flammable (F, R 11).  
 Acute oral toxicity: harmful (Xn, R 22).  
 Skin sensitisation (Xi, R 43).  
 Aquatic environmental hazard, chronic toxicity: harmful (R 52/53).

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS02

Signal Word :

DANGER

Product identifiers :

EC 265-192-2

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.

006-081-00-9

ZINC BIS(DIBUTYLDITHIOCARBAMATE)

Hazard statements :

H225

Highly flammable liquid and vapour.

H302

Harmful if swallowed.

H317

May cause an allergic skin reaction.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
 P261 Avoid breathing vapours.  
 P264 Wash hands thoroughly after handling.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

## Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P330 Rinse mouth.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

## Precautionary statements - Storage :

P403 + P235 Store in a well-ventilated place. Keep cool.

## Precautionary statements - Disposal :

P501 Dispose of contents/container at a disposal facility in accordance with local regulations.

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

## Hazard symbols :



Harmful



Highly flammable

## Contains :

006-081-00-9

ZINC BIS(DIBUTYLDITHIOCARBAMATE)

EC 265-192-2

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.

## Risk phrase :

R 52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 43

May cause sensitisation by skin contact.

R 22

Harmful if swallowed.

R 11

Highly flammable.

## Safety phrase :

S 24

Avoid contact with skin.

S 37

Wear suitable gloves.

S 16

Keep away from sources of ignition - No smoking.

S 23

Do not breathe vapour.

S 60

This material and its container must be disposed of as hazardous waste.

S 62

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**2.3. Other hazards**

No data available.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.1. Substances**

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) n° 1907/2006.

**3.2. Mixtures****Composition :**

Identification	Name	Classification	%
CAS: 64742-89-8 EC: 265-192-2 REACH: 05-2114107985-43	SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.	GHS07, GHS08, GHS02, Dgr Xn,F H:225-302-304 R: 65-22 NOTA: H P	50 <= x % < 100
INDEX: 006-081-00-9 CAS: 136-23-2 EC: 205-232-8	ZINC BIS(DIBUTYLDITHIOCARBAMATE)	GHS07, GHS09, Wng Xi,N H:319-335-315-317-410 R: 36/37/38-43-50/53	1 <= x % < 2.5
CAS: 9006-04-6 EC: 232-689-0	NATURAL RUBBER	GHS08, Dgr Xn H:334-413	0 <= x % < 1

R: 42-53

**Information on ingredients :**

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures****In the event of splashes or contact with eyes :**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non fire-fighters**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

**For fire-fighters**

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep the container tightly closed in a dry, well-ventilated place

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
9006-04-6	0.001 mg/m <sup>3</sup>	-	-	-	I

- Switzerland (SUVA 2009) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Temps :	RSB :
9006-04-6	-	-	-	-	-	S

### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state :	viscous liquid.
------------------	-----------------

#### Important health, safety and environmental information

pH :	Not relevant.
Boiling point/boiling range :	> 35°C
Flash Point :	-7.00 °C.
Explosive properties, lower explosivity limit (%) :	1.3
Explosive properties, upper explosivity limit (%) :	8
Vapour pressure :	Below 110 kPa (1.10 bar).

Vapour density :	>1 (Air=1)
Density :	< 1
Water solubility :	Insoluble.
Viscosity :	~ 540 mm <sup>2</sup> /s
Evaporation rate :	3.5 (BuAc=1)

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

**10.5. Incompatible materials**

Keep away from :

- oxidising agents
- oxidising material

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

**11.1.1. Substances****Acute toxicity :**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS: 64742-89-8)

Oral route : DL50 = 2000 mg/kg

Species : Rat

**11.1.2. Mixture**

No toxicological data available for the mixture.

**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity****12.1.1. Substances**

No aquatic toxicity data available for the substances.

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK) :**

WGK 1 (VwVwS vom 27/07/2005, KBws) : Slightly hazardous for water.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2011 - IMDG 2010 - ICAO/IATA 2012).

**14.1. UN number**

1133

**14.2. UN proper shipping name**

UN1133=ADHESIVES containing flammable liquid

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

II

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	640DC	E2	2	D/E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	3	-	II	5 L	F-E,S-D	-	E2			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	II	353	5 L	364	60 L	A3	E2	
	3	-	II	Y341	1 L	-	-	A3	E2	

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Particular provisions :**

No data available.

**- German regulations concerning the classification of hazards for water (WGK) :**

Germany : WGK 1 (VwVwS vom 27/07/2005, KBws)

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Title for H, EUH and R indications mentioned in section 3 :**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
R 22	Harmful if swallowed.
R 36/37/38	Irritating to eyes, respiratory system and skin.
R 42	May cause sensitization by inhalation.
R 43	May cause sensitisation by skin contact.
R 50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 53	May cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed.

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark