


Product Name

**Qm**  
(External driver)

Technical description

Adjustable floodlight suitable for wall or ceiling application, designed to produce direct or indirect light. It has a low visual impact. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket. Screws made of AISI 304 stainless steel. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic optical PC.



Supply

External driver (also in dimmable or DALI versions).  
Voltage 220-240V AC 50/60Hz.  
Temperature -40° +45°

Installation

Wall and ceiling

Applications

Big boards, shop window, facades decoration

Size (mm)


211 x 233 x 73,5

Colour

Dark grey **4**

Decay of the luminous flux

≥100.000 hr L90B10



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
<b>L00QM40H6BL40050</b>	LED	50 W	5500 lm	8000 lm	4000 K	>80	H6	Dark grey	-
<b>L00QM40H6DI40050</b>	LED	50 W	5500 lm	8000 lm	4000 K	>80	H6	Dark grey	Dimmer
<b>L00QM40H6DA40050</b>	LED	50 W	5500 lm	8000 lm	4000 K	>80	H6	Dark grey	DALI

Accessories



Pole connection B  
LKITA000000401 09



Fast connector  
IP 3 poles  
LKITA00000000003



Cable with connector  
Ca. 2m/Co. IP 2 poli  
LKITA00000000040  
Ca. 2m/Co. IP 3 poli  
LKITA00000000041

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.