


Product Name

Qm
(External driver)

Technical description

Adjustable floodlight suitable for wall or ceiling application, designed to produce direct or indirect light. It has a low visual impact. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket. Screws made of AISI 304 stainless steel. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic optical PC.



Supply

External driver (also in dimmable or DALI versions).
Voltage 220-240V AC 50/60Hz.
Temperature -40° +45°

Installation

Wall and ceiling

Applications

Big boards, shop window, facades decoration

Size (mm)


211 x 233 x 73,5

Colour

Dark grey **4**

Decay of the luminous flux

≥100.000 hr L90B10



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00QM40HABL40050	LED	50 W	5500 lm	8000 lm	4000 K	>80	HA	Dark grey	-
L00QM40HAD140050	LED	50 W	5500 lm	8000 lm	4000 K	>80	HA	Dark grey	Dimmer
L00QM40HADA40050	LED	50 W	5500 lm	8000 lm	4000 K	>80	HA	Dark grey	DALI

Accessories



Pole connection B
LKITA000000401 09



Fast connector
IP 3 poles
LKITA00000000003



Cable with connector
Ca. 2m/Co. IP 2 poli
LKITA00000000040
Ca. 2m/Co. IP 3 poli
LKITA00000000041

LANZINI indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.