

Product Name

Qs
(Linear)

Technical description

Adjustable floodlight suitable for wall or ceiling application, designed to produce direct or indirect light. It has a low visual impact. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket. Screws made of 18/10 stainless steel. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic optical PC.



Supply

Driver included linear.
Input voltage 230 V AC 50Hz.
Temperature -40° +45°

Installation

Wall and ceiling.

Applications

Big boards, facades decoration, shop windows.

Size (mm)



155 x 171 x 32

Colour

Dark grey **4**

Decay of the luminous flux

≤50.000 hr L85B15



0,7 Kg

Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour
L00QS4060L140010	LED	10 W	979 lm	1450 lm	4000 K	>80	60°	Dark grey

Accessories



Pole connection B
LKITA00000040109



Fast connector
IP 3 poles
LKITA0000000003



Ground spike
support kit
LKITA0000000022

LANZINI indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.