


Coho® Thru Axle Fit Guide

This product is NOT compatible with capped drop outs.

This guide is intended to help determine which Coho® Thru Axle you will need for hitching the Coho® XC Cargo Trailer to your bike.


1

Print this sheet at 100% on 8.5" X 11" paper. Verify the illustration is to scale by using a ruler.




2

Confirm the thread pitch of your current axle by placing it over the illustrations below to find a match. The thread pitch is the distance from the tip of one thread to the tip of the next. If you are unable to confirm the thread pitch using this guide, please contact your bike manufacturer for assistance.



3

Measure the length of your current thru axle using this illustration. Align your axle at 0mm, measure from the base of the axle head to the tip of the threads.



4

Use the thread pitch and axle length to determine which model Coho Thru Axle axle you need.

note

If your axle length is not shown for the thread pitch you have, we do not have a compatible thru axle for you at this time.

Thread Pitch (TP)	Frame Measured Axle Length	Compatible Burley Coho Thru Axle	SKU
1.0	~158-174mm	12 X 1.0, 158-174mm	960250
1.0	~229mm	12 X 1.0, 219-229mm	960225
1.5	~159-165mm	12 X 1.5, 159-165mm	960252
1.5	~172-178mm	12 X 1.5, 172-178mm	960253
1.5	~209mm	12 X 1.5, 209mm	960226
1.5	~229mm	12 X 1.5, 229mm	960215
1.75	~174-180mm	12 X 1.75, 174-180mm	960214
1.75	~192-198mm	12 X 1.75, 192-198mm	960228
1.75	~209mm	12 X 1.75, 209mm	960227
1.75	~229mm	12 X 1.75, 229mm	960216