

Latex Exam Gloves



Features and Benefits

- Elastic and highly flexible for exceptional comfort and dexterity.
- Cream Color.
- Powder Free.
- Medical Grade.
- Single Use Only.
- Textured surface for improved grip.
- Complies with FFDCA food handling requirements 21 CFR, Parts 170-199.

Specifications



Usage



Ordering Information

ITEM NUMBER	SIZE	FINGER THICKNESS	PALM THICKNESS	GRAM WEIGHT*	INNER BOX	OUTER CASE
A31A11	SM	5.5 mil +/- 0.5 mil	4.5 mil +/- 0.5 mil	6.0g +/- 0.2g	8-50001-98124-8	008-50001-98125-5
A31A12	MD				8-50001-98127-9	008-50001-98128-6
A31A13	LG				8-50001-98130-9	008-50001-98131-6
A31A14	XL				8-50001-98133-0	008-50001-98134-7

*Based on size M

ITEM NUMBER	QUANTITY	INNER BOX DIMENSIONS	CASE DIMENSIONS	TI/HI	CASE WEIGHT (LBS.)	COUNTRY OF ORIGIN
A31A11	100/bx 10 bx/cs	9.1 x 4.7 x 2.6"	13.6 x 9.8 x 9.3"	14/7	14.1	Indonesia
A31A12					15.2	
A31A13					16.3	
A31A14					17.4	

Finding the right hand protection doesn't have to be complicated. Consider VGuard® gloves as an extension of our promise to you: High quality products, great value and excellence in service. If ever you have a question regarding which glove is best for your application, we're here to help. VGuard® is protection you can count on!

Vanguard Safety

Cumming, GA 30041 • 1-866-VGUARD-6 (1-866-848-2736)
 Info@VanguardSafety.com • www.VanguardSafety.com

Latex Exam Gloves



Composition

Material:	Natural Rubber Latex
Allergen content:	Less than 200 µg/dm ² as per ASTM D5712
Powdered:	No, as per ASTM D6124

Quality

Quality Control:	ASTM D3578, ASTM F1671
Quality Assurance:	ISO:9001, ISO:13485
Regulatory Compliance:	FDA Approved

Technical Data

THICKNESS	MIL
Palm:	4.5 ± 0.5
Finger:	5.5 ± 0.5

Weight*:	6.0 gm ± 0.2 gm
-----------------	-----------------

*Based on size M

PHYSICAL PROPERTIES	BEFORE AGING	AFTER AGING
Tensile Strength (MPa):	Min. 14	Min. 14
Ultimate Elongation (%):	Min. 650	Min. 500
Freedom from holes:	AQL 2.5	N/A

DIMENSIONS			
ITEM NO.	SIZE	PALM WIDTH (mm)	LENGTH (mm)
A31A11	Small	80 ± 10	Min. 220
A31A12	Medium	95 ± 10	Min. 230
A31A13	Large	110 ± 10	Min. 230
A31A14	XL	120 ± 10	Min. 230

COUNTRY OF ORIGIN	HARMONIZATION CODE
Indonesia	4015.12.1010

Vanguard Safety

Cumming, GA 30041 • 1-866-VGUARD-6 (1-866-848-2736)
Info@VanguardSafety.com • www.VanguardSafety.com