

### Philips Signage Solutions Q-Line Display

**43"** Direct LED Backlight Ultra HD

## **Signage**Solutions



### 43BDL3511Q

# Stand out

### Easy-setup 18/7 display.

Inform and enthral with a Philips Q-Line Professional Ultra HD Display. This reliable solution can be up and running as quickly as you need.

### Effortless setup. Total control.

- Operate, monitor and maintain with CMND and Control
- Schedule what you want, when you want with SmartPlayer

### **Cost-effective system solution**

- Energy-saving automatic backlight control
- Integrated media player. Easily schedule USB content
- FailOver ensures that content is always playing
- Easy control. Remotely manage networked displays

### Superb picture. Ultra-high brightness.

• Ultra-HD. Rich images. Stunning contrast



## Highlights

#### **CMND** and Control



Run your display network over a local (LAN) connection. CMND and Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

#### FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs, ensuring that content keeps playing even if the primary source goes down. Simply set a list of alternative inputs to be sure your business is always on.

#### Integrated media player

Easily schedule content to play from USB. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback has finished.

#### **SmartPlayer**



Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.





## Specifications

#### **Picture/Display**

- Diagonal screen size: 42.5 inch / 108 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 400 cd/m<sup>2</sup>
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 0.2451 x 0.2451 mm
- Display colours: 1.07 Billion
- Panel technology: IPS
- Contrast ratio (typical): 1200:1
- Clinical image: D-Image preset (dicom part 14 compatible)

Refresh rate

70 Hz

75 Hz 60, 70, 75 Hz

75 Hz

75 Hz

60 Hz

50 Hz

50 Hz

60 Hz

30Hz

60 Hz

50, 60 Hz

50, 60 Hz

• Video input: DVI-I (x 1), HDMI 2.0 (x 2), USB 2.0

• External control: IR (in/out) 3.5 mm jack, RJ45,

• Placement: Landscape (18/7), Portrait (18/7)

· Signal loop through: RS232, IR Loop through

· Energy-saving functions: Smart Power

Refresh rate

60, 67, 72, 75 Hz

56, 60, 72, 75 Hz

• Haze: 1%

Resolution

640 x 480

720 x 400

 $800 \times 600$ 

832 x 624

1024 x 768

1152 x 864

1152 x 870

1280 x 720

1280 × 800

1280 x 1024

1440 x 900

1600 x 1200

1680 x 1050

1920 x 1080

Video formats

Resolution

480i

480p

576p

576i

720p

1080i

1080p

(x 2)

3840 x 2160

3840 x 2160

Connectivity

Convenience

• Audio input: 3.5 mm jack • Audio output: 3.5 mm jack

RS232C (in/out) 2.5 mm jack

• Tiled Matrix: Up to 10 x 15

#### **Supported Display Resolution** Computer formats

- Standby power consumption: <0.5 W</li>
- Mains power: 100-240 V~, 50/60 Hz
- Power Saving Features: Smart Power
- Energy Label Class: G

#### Sound

• Built-in speakers: 2 x 10 W RMS

#### Accessories

- Stand: BM05922(optional)
- Philips logo (x 1), AC power cord, AC Switch Cover, Quick start guide (x 1), Remote control and AAA batteries, RS232 daisy chain cable (x 1), USB Cover and screw x 1, Wire Clamper (x 3)

#### **Miscellaneous**

- French, German, Italian, Japanese, Polish, Russian, Spanish, Simplified Chinese, Turkish, Traditional Chinese
- Regulatory approvals: CE, FCC, Class A, CB, BSMI, VCCI, CU, ETL, EMF, PSB
- Warranty: 3 year warranty

#### **Multimedia Applications**

- USB Playback Video: H.264, JPEG, MPEG, WMV3
- USB Playback Audio: AAC, WMA, MPEG, HEAAC

#### Dimensions

- Set dimensions (W x H x D):
- 973.0 x 561.2 x 63.5 mm
- Set dimensions in inch (W x H x D): 38.31 x 22.09 x 2.50 inch
- Bezel width: 13.9 mm (Even bezel)
- Wall Mount: 200mm x 200mm, M6
- Product weight: 10.7 kg
- Product weight (lb): 23.59 lb



Issue date 2022-07-15 © 2022 Koninklijke Philips N.V. All Rights reserved. Version: 1.0.1 Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners. 12 NC: 8670 001 78302 EAN: 87 12581 77857 6 www.philips.com

- Network controllable: RS232, RI45 · Keyboard control: Hidden, Lockable • Remote control signal: Lockable
- · Start-up: Switch on delay, Switch on status, Boot on source

3BDL35110/00

• Start-up window: enable/disable Philips logo

#### **Operating conditions**

- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- Altitude: 0 ~ 3000 m
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20~80% RH (No condensation)
- Humidity range (storage) [RH]: 5~95% RH (No condensation)

#### Power

- Consumption (Typical): 105 W
- Consumption (Max): 155 W

- Included Accessories: IR sensor cable (1.8 m) (x 1),
- On-Screen Display Languages: Arabic, English,

- USB Playback Picture: BMP, JPEG, PNG